

Technical sheet :

# **WRAPPED BALE CLAMP (COMPACT MACHINES)**

---



## **Customer benefits**

- Easy to use and competitive attachment.
- Powerful double effect cylinder allows the manipulation of very heavy bales.
- Rounded and articulated clamp designed to fit the shape of every bale.
- Smooth structure that avoids any perforation of plastic film.

## **Technical characteristics**







- Self-lubricated anti-wear ring that improves the longevity of the attachment.
- Excellent lifting capacity up to 1000 kg.
- Welded monobloc chassis.
- Handles wrapped bale with diameter from 1 m to 1,7 m.

[The 3D picture at the top of this page is the reference CLBW 800 - N51502013].

**MANITOU GROUP ATTACHMENTS**

Technical characteristics		CLBW 800	
Distance to center of gravity (mm)		441	
Capacities			
Capacity (kg)		800	
Weight			
Overall weight (kg)		227	
Weight and dimensions			
Overall height (mm)	h17	810	
Overall length (mm)	l1	1310	
Width (mm)		1587	
Diameter minimum / Diameter maximum (mm)		820 / 1504	
Working Parameters			
Machine Equipment			
Opening minimum (mm)		249	
Opening maximum (mm)		1053	

Machines compatibility		CLBW 800	
All-Tach® Narrow		N51502697	
All-Tach®		N51502013	
4 point Carriage		N51502429	
Euro Carriage		N51502430	
AL420		X	
AL430		X	
AL530		X	
AL550		X	
GCT 3-14		X	
GCT 3-14 +		X	
MLA 4-50 H		X	
MLA 4-50 H-C		X	
MLA 5-50 H		X	
MLA 5-60 H-Z		X	
ULM 412 H		X	
ULM 412 H		X	
ULM 415 H		X	
ULM 415 H		X	
MLA 3-35 H <small>OLD</small>		X	
MLA 4-50 H <small>OLD</small>		X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes