

Technical sheet :

WRAPPED BALE CLAMP (COMPACT MACHINES)



Customer benefits

- Easy to use and competitive attachment.
- Powerful double effect cylinder allows the manipulation of very heavy bales.
- Rounded and articulated clamp designed to fit the shape of every bale.
- Smooth structure that avoids any perforation of plastic film.

Technical characteristics







- Self-lubricated anti-wear ring that improves the longevity of the attachment.
- Excellent lifting capacity up to 1000 kg.
- Welded monobloc chassis.
- Handles wrapped bale with diameter from 1 m to 1,7 m.

[The 3D picture at the top of this page is the reference CLBW 800 - N51502013].

MANITOU GROUP ATTACHMENTS

Technical characteristics		CLBW 800
Distance to center of gravity (mm)		441
Capacities		
Capacity (kg)		800
Weight		
Overall weight (kg)		227
Weight and dimensions		
Overall height (mm)	h17	810
Overall length (mm)	l1	1310
Width (mm)		1587
Diameter minimum / Diameter maximum (mm)		820 / 1504
Working Parameters		
Machine Equipment		
Opening minimum (mm)		249
Opening maximum (mm)		1053

Machines compatibility	CLBW 800
All-Tach® Narrow	N51502697
All-Tach®	N51502013
4 point Carriage	N51502429
Euro Carriage	N51502430
AL420	X
AL430	X
AL530	X
AL550	X
GCT 3-14	X
GCT 3-14 +	X
MLA 4-50 H	X
MLA 4-50 H-C	X
MLA 5-50 H	X
MLA 5-60 H-Z	X
ULM 412 H	X
ULM 412 H	X
ULM 415 H	X
ULM 415 H	X
MLA 3-35 H <small>OLD</small>	X
MLA 4-50 H <small>OLD</small>	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes