

1640 E

COMPACT LOADERS



Key Features

- ✓ Ultra-Compact Skid Loader
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat
- ✓ Lightweight for Easy Transport

Key Specifications

- ✓ Operating capacity (50%) - 386 kg (850 lbs.)
- ✓ Overall height to top of ROPS - 1897 mm (74.7")
- ✓ 909 mm (35.8") maximum width - less bucket
- ✓ Gross Power - 18.1 kW (24 hp) @ 2400 rpm
- ✓ Yanmar / 3TNV82A-BPMSR / Stage V Compliant
- ✓ 86 Nm (68 ft.-lbs.) @ 1200 rpm max torque
- ✓ 2438 mm (96") height to hinge pin
- ✓ 1352 kg (2,980 lbs.) operating weight

ESPECIFICACIONES

		MÉTRICO
Capacities	Operating Capacity At 50% Tipping Load	386 kg
	Operating Weight	1351.70 kg
	Tipping capacity	711.10 kg
Weight and dimensions	Wheelbase	775 mm
	Overall Operating Height - Fully Raised	3167 mm
	Height to Hinge Pin - Fully Raised	2438 mm
	Overall Height to top of ROPS	1897 mm
	Dump angle at full height	46 °
	Dump height	1836 mm
	Overall length with bucket	2576 mm
	Dump reach - Full height	376 mm
	Rollback at ground	30 °
	Seat to ground height	879 mm
	Overall width less bucket	909 mm
	Bucket Width	914 mm
	Ground clearance	150 mm
	Overall length - Less Bucket	1905 mm
	Clearance Radius - Front with Bucket	1473 mm
Rear departure angle	23 °	
Performances	Travel speed (unladen)	8.90 km/h
Wheels	Standard tires	8.70 x 12
Engine	Engine brand	Yanmar
	Engine model	3TNV82A-BPMSR
	Engine norm	Stage V
	Gross Power	18.10 kW
	Net Power	17.90 kW
	Max. torque / Engine rotation	86 Nm / 2400 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	1.70 kW
Hydraulics	Standard flow - Auxiliary hydraulics	38.20 l/min
Tank capacities	Fuel tank	29 l
	Hydraulic tank capacity	27.30 l
	Displacement	1.30 l



One Gehl Way, West Bend, WI 53095
Teléfono: (262) 334-9461



GEHL COMPACT EQUIPMENT

® Representa registro en los Estados Unidos. Las marcas comerciales pueden o no estar registradas en otros países.