1640 E

SKID LOADERS



GEHL®

Capacities		Metrisch	US-System
Operating Capacity At 50% Tipping Load		386 kg	851 lb
Operating Weight		1351.70 kg	2980 lb
Tipping capacity		711.10 kg	1568 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3167 mm	125 in
Height to Hinge Pin – Fully Raised	h28	2438 mm	96 in
Overall Height to top of ROPS	h17	1897 mm	75 in
Dump angle at full height	a5	46 °	46 °
Dump height	h29	1836 mm	72 in
Overall length with bucket	l16	2576 mm	101 in
Dump reach - Full height	r6	376 mm	15 in
Rollback at ground	a13	30 °	30 °
Seat to ground height	h30	879 mm	35 in
Wheelbase	у	775 mm	31 in
Overall width less bucket	b1	909 mm	36 in
Bucket Width	e1	914 mm	36 in
Ground clearance	m4	150 mm	6 in
Overall length - Less Bucket	l2	1905 mm	75 in
Clearance Radius - Front with Bucket	b18	1473 mm	58 in
Clearance Circle - Front without Bucket	b19	833 mm	33 in
Clearance Circle - Rear	wa1	1097 mm	43 in
Performances			
Travel speed (unladen)		8.90 km/h	6 mph
Wheels			
Standard tires		8.70 x 12	8.70 x 12
Engine			
Engine brand		Yanmar	Yanmar
Engine model		3TNV82A-BPMSR	3TNV82A-BPMSR
Engine norm		Stage V	Stage V
Gross Power		18.10 kW	18.10 kW
Net Power		17.90 kW	17.90 kW
Max. torque / Engine rotation		86 Nm / 2400 rpm	63 ft/lbs / 2400 rpm
Power source		Diesel	Diesel
Battery voltage		12 V	12 V
Starter		1.70 kW	1.70 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		38.20 l/min	10 US gpm
Tank capacities			
Fuel tank		29 l	8 US gal
Hydraulic tank capacity		27.30 l	7 US gal
Displacement		1.30 l	0.34 US gal





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend