1640 E

SKID LOADERS



GEHL®

Capacities Metrich Rated Operating Qaacity 386 kg Unlader weight 1352 kg Weight and dimensions 152 kg Overall Operating Feight - Fully Raised h.22 3167 mm Uneyall Height to Up of ROPS h.72 386 kg Dump apige at full height 5.5 4.6° Dump apige at full height 5.5 4.6° Dump height 16 2576 mm Overall length with bucket 16 376 mm Dump neight 16 376 mm Oberall Length with bucket 16 376 mm Dump neight 16 376 mm Owerall kingth to be ket 18 2576 mm Dump neight 16 376 mm Oweral kingth to be ket 18 2576 mm Dump neight for put he ket 18 375 mm Oweral kingth count of kets 18 90° mm Bucket With e1 94 mm Ground clearance pt 195 mm Glearance Agent for put he ket 18		.0.01 2.000	t am 4: Mai 2024 am 00:00:50 010
Unlader weight 1352 kg Weight and dimensions 127 Overall Operating Height - Fully Raised h.28 2438 mm Overall Height to Usinge Pin - Fully Raised h.28 2438 mm Dump angle at full height a5 46 ° Dump page at full height a5 46 ° Dump height hbp 1386 mm Overall leight with bucket f6 376 mm Dump rasch - Full height a6 376 mm Overall leight with bucket a1 2576 mm Dump rasch - Full height a6 376 mm Overall leight with bucket a1 30 ° Seat to ground a3 30 ° Seat to ground height h30 879 mm Wheelbase y 775 mm Overall width less bucket b1 900 mm Bucket With e1 94 mm Ground clearance m4 150 mm Overall leight - Less Bucket b18 1473 mm Clearance Circle - Front without Bucket b18 1473 mm </th <th>Capacities</th> <th></th> <th>Metrisch</th>	Capacities		Metrisch
Weight and dimensions 1.27 3.167 mm Overall Operating Height - Fully Raised h.28 2.438 mm Overall Height to top of ROPS h.17 1897 mm Dump naged at full Height h.29 1836 mm Dump neight h.129 1836 mm Overall leight with bucket h.16 2.756 mm Dump reach - Full height n.6 3.76 mm Rollback at ground a.13 3.0° Seat to ground height h.30 8.79 mm Wheelbase y 7.75 mm Overall width less bucket b.1 9.99 mm Wacket Width e.1 9.99 mm Bucket Width e.1 9.99 mm Woreall eight - Less Bucket p.1 9.99 mm Uceal leight - Less Bucket p.1 9.99 mm Clearance Circle - Front with Bucket p.1 9.90 mm Clearance Circle - Front without Bucket p.1 9.90 mm Clearance Circle - Front without Bucket p.9 8.90 km/h Webeat p.80 km/h 9.90 mm <tr< td=""><td>Rated Operating Capacity</td><td></td><td>386 kg</td></tr<>	Rated Operating Capacity		386 kg
Overall Operating Height - Fully Raised h.27 3167 mm Height to Kinge Pin - Fully Raised h.28 2.438 mm Overall Height to Kinge Pin - Fully Raised h.77 1897 mm Dump pagle at full height a5 46 ° Dump pagle at full height 186 2.276 mm Overall leight with bucket 116 2.276 mm Dump reach - Full height 16 3.76 mm Rollback at ground a13 3.0° Seat to ground height h.30 879 mm Wheelbase y 7.75 mm Overall leight - Less bucket pl 9.77 mm Overall leight - Less bucket pl 19.00 mm Overall leight - Less bucket pl 8.00 mm Overall leight - Less bucket pl 8.00 mm Overall leight - Less bucket pl 8.00 mm Clearance Gircle - Rear pl	Unladen weight		1352 kg
Height to binge Fin - Fully Raised h28 2438 mm Overall Height to top of ROPS 45 46° Dump nageat full height a5 46° Dump height 166 25' 6 mm Overall length with bucket 166 376 mm Overall length with bucket 166 376 mm Rollback at ground a13 30° Seat to ground height h30 879 mm Wheelbase y 75 mm Overall width less bucket 91 900 mm Bucket Width e1 900 mm Bucket Width e2 100 mm Gearance Gircle - Front without Bucket e1	Weight and dimensions		
Overall Height to top of ROPS h7 1897 mm Dump angle at ful height a5 46° Dump height h29 1836 mm Overall length with bucket t6 2976 mm Dump reach - Full height r6 376 mm Rollback at ground at3 30° Seat tog round height b3 879 mm Wheelbase y 775 mm Overall width less bucket b1 909 mm Bucket Width e1 94 mm Ground clearace m4 150 mm Glearace Gride- Front with Bucket b1 170 mm Clearace Gride- Front with Bucket b1 187 mm Clearace Gride- Front without Bucket b1 8.70 x tz Tawel speed (unladen) x 8.70 x tz	Overall Operating Height - Fully Raised	h27	3167 mm
Dump angle at full height a5 46° Dump height 129 1336 mm Overall length with bucket 116 2576 mm Dump reach - Full height a6 376 mm Rollback at ground a6 376 mm Rollback at ground height a50 879 mm Wheelbase y 775 mm Overall width less bucket b1 909 mm Bucket Width e1 94 mm Ground clearance a6 94 mm Ground clearance b1 909 mm Overall length - Less Bucket a6 94 mm Ground clearance b2 1905 mm Overall length - Less Bucket b1 1909 mm Clearance Gride - Front with Bucket b1 1909 mm Clearance Gride - Front with Bucket b18 1473 mm Clearance Gride - Front without Bucket b1 9 80 mm Taward Speed (unladen) 6 8.0 mm 80 mm Wheels 1 8.0 mm 8.0 mm Eng	Height to Hinge Pin – Fully Raised	h28	2438 mm
Dump height h29 1836 mm Overall leight with bucket 16 2576 mm Dum preach - Full height 16 376 mm Röllback at ground at3 30° Seat to ground height y 775 mm Wheelbase y 775 mm Overall width less bucket b1 99 mm Bucket Width b1 99 mm Ground clearace m4 150 mm Overall leight - Less Bucket b1 990 mm Guerance Gircle - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b18 1473 mm Clearance Circle - Rear wat 1099 mm Tavel speed (unladen) wat 89 km/h Whees 80 km/h 89 km/h Standard tires 8 80 km/h 80 km/h Engine brand 8 8 70 km 8 8 80 km/h Engine brand 8 8 km/can 8 8 km/can Engine norm 8 8 km/can 8 8 km/can Fross Power 8 8 km/can 8 8 km/can<	Overall Height to top of ROPS	h17	1897 mm
Overall length with bucket 116 2576 mm Dump reach - Full height 6 376 mm Rollback at ground a33 30° Seat to ground height h30 879 mm Wheelbase y 775 mm Overall width less bucket b1 999 mm Bucket Width e1 914 mm Ground clearance b2 1905 mm Overall length - Less Bucket L2 1905 mm Clearance Gride - Front with bucket L2 1905 mm Clearance Gride - Front with bucket b18 1473 mm Clearance Gride - Front with bucket b19 833 mm Clearance Gride - Front with bucket b19 833 mm Clearance Gride - Front with bucket b19 830 km/h Reformances b19 833 mm Clearance Gride - Front without bucket b19 830 km/h Wheels b1 80 km/h Tavel speed (unlader) 5 80 km/h Wheels 5 370 km/h Engine Dard 5 <td>Dump angle at full height</td> <td>a5</td> <td>46 °</td>	Dump angle at full height	a5	46 °
Dump reach - Full height r6 376 mm Rollback at ground a13 30° Seat to ground height h30 879 mm Wheelbase y 775 mm Overall width less bucket b1 999 mm Bucket Width e1 914 mm Ground clearance m 150 mm Guerlance Radius - Front with Bucket b18 1905 mm Clearance Riche - Front with Bucket b18 1473 mm Clearance Gricle - Rear b18 1933 mm Clearance Gricle - Rear b19 839 km/h Tavel Speed (unladen) wa1 1907 mm Wheels 8.90 km/h 8.90 km/h Standard tires 8.90 km/h 8.90 km/h Engine brand 5 370×22 mm Engine model 5 370×22 mm Engine model 5 1530 km Engine norm 5 1530 km Nev Power 5 88 hm// 2400 rpm Power source 5 88 hm// 2400 rpm Ba	Dump height	h29	1836 mm
Rollack at ground a13 30° Seat to ground height h30 879 mm Wheelbase y 775 mm Overall width less bucket b1 909 mm Bucket Width e1 914 mm Ground clearance m4 150 mm Overall leight - Less Bucket 12 1905 mm Clearance Radius - Front with Bucket b18 1473 mm Clearance Gircle - Front without Bucket b18 1473 mm Clearance Gircle - Rear b19 833 mm Clearance Gircle - Front without Bucket b18 1473 mm Clearance Gircle - Front without Bucket b19 833 mm Clearance Gircle - Front without Bucket b18 1473 mm Clearance Gircle - Front without Bucket b18 1473 mm Clearance Gircle - Front without Bucket b18 1873 mm Clearance Gircle - Front without Bucket b18 8.90 km/h Wheels 18 8.90 km/h 18.00 km Standard Its season 18.00 km 18.00 km Engine brand	Overall length with bucket	l16	2576 mm
Seat to ground height h30 879 mm Wheelbase y 775 mm Overall width less bucket b1 909 mm Bucket Width e1 914 mm Ground clearance m4 150 mm Overall length - Less Bucket b18 1473 mm Clearance Addius - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b19 833 mm Clearance Circle - Rear wa1 1997 mm Performance wa1 1997 mm Tavel speed (unladen) wa1 8.70 x 12 Performance sextract 8.70 x 12 Engine brand sextract 8.70 x 12 Engine brand sextract 3170 x 32 Engine model sextract 3180 km Engine model sextract 3180 km Bet Power sextract 18.0 km Max. torque / Engine rotation sextract 86 Nn / 2400 rpm Power source sextract 12 V Battery voltage sextract	Dump reach - Full height	r6	376 mm
Wheebase y 775 mm Overall width less bucket b1 999 mm Bucket Width e1 994 mm Ground clearance m4 150 mm Overall length - Less Bucket b2 1905 mm Clearance Radius - Front with Bucket b18 W33 mm Clearance Circle - Front with Bucket b18 833 mm Clearance Circle - Front with bucket wat 1097 mm Clearance Circle - Front with Bucket wat 1097 mm Clearance Circle - Front with Bucket wat 1097 mm Clearance Circle - Front with Bucket wat 1097 mm Clearance Circle - Front with Bucket wat 1097 mm Clearance Circle - Front with Bucket wat 1097 mm Clearance Circle - Front with Bucket 8 8 9 Problemed - 8 - 8 1097 mm Wheeb - \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1 \$1	Rollback at ground	a13	30 °
Overall width less bucket 51 909 mm Bucket Width e1 914 mm Ground clearance m4 150 mm Overall length - Less Bucket 12 1905 mm Clearance Radius - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b18 1473 mm Clearance Circle - Rear b19 333 mm Clearance Circle - Rear b19 383 mm Performances b19 8.90 km/h Travel speed (unladen) b2 8.90 km/h Wheek 5 8.90 km/h Standard tires 5 8.70 x t2 Engine brand 5 \$ 31NM23A-BPMSR Engine norm 5 \$ 31NM23A-BPMSR Engine norm 5 \$ 18,10 kW Ket Power 5 \$ 5 km / 2400 rpm Next Power 5 \$ 5 km / 2400 rpm Battery voltage 5 \$ 5 km / 2400 rpm Starter 5 \$ 12 V Starter 5 \$ 12 V S	Seat to ground height	h30	879 mm
Bucket Width e1 914 mm Ground clearance m4 150 mm Overall length - Less Bucket m4 150 mm Clearance Adrius - Front with Bucket b18 1473 mm Clearance Gricle - Front without Bucket b19 833 mm Clearance Gricle - Rear wal 1007 mm Performances wal 8.90 km/h Travel speed (unladen) wal 8.90 km/h Wheels \$ 8.70 x 12 Standard tires \$ \$ 8.70 x 12 Engine Brand \$ \$ \$ 12 \$ 12 \$ 12 \$ 12 \$ \$ 12 \$ </td <td>Wheelbase</td> <td>у</td> <td>775 mm</td>	Wheelbase	у	775 mm
Ground clearance m4 150 mm Overall length - Less Bucket 12 1905 mm Clearance Radius - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b19 833 mm Clearance Circle - Rear wa1 1097 mm Performances Travel speed (unladen) wa1 8.90 km/h Wheels 8.70 x 12 8.70 x 12 Engine 370 x 12 8.70 x 12 Engine brand 5 37 x mm Engine model 37 x x mm 37 x x x x x x x x x x x x x x x x x x x	Overall width less bucket	b1	909 mm
Overall length - Less Bucket 12 1905 mm Clearance Radius - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b19 833 mm Clearance Circle - Rear wa1 1997 mm Performance wa1 1997 mm Travel speed (unladen) wa 8.90 km/h Wheels Standard tires 8.90 km/h Standard tires 5 \$370 x 12 Engine 5 \$370 x 12 Engine model \$1 \$370 x 12 Engine norm \$1 \$310 kW Net Power \$1 \$13.0 kW Net Power \$2 \$13.0 kW Nature / Engine rotation \$6 km / 2400 rpm \$6 km / 2400 rpm Power source \$2 \$2 ty Statery \$2 ty \$1.70 kW Hydraulics \$2 \$1.70 kW Statery Outage \$2 \$2 ty Standard flow - Auxiliary hydraulics \$3.820 l/min Tank capacities \$2 \$2	Bucket Width	e1	914 mm
Clearance Radius - Front with Bucket b18 1473 mm Clearance Circle - Front without Bucket b19 833 mm Clearance Circle - Rear wa1 1097 mm Performance Travel speed (unladen) 8.90 km/h Wheels 8.70 x 12 Standard tires 9 \$8.70 x 12 Engine \$1 \$1 mm Engine brand \$2 \$2 mm Engine norm \$31NW52A-BPMSR Engine norm \$1.50 kW Net Power \$1.7.90 kW Nex Lorque / Engine rotation \$6 mm / 2400 rpm Power source \$0 \$6 mm / 2400 rpm Battery voltage \$1.70 kW Starder \$1.70 kW Hydraulics \$38.20 l/min Standard flow - Auxiliary hydraulics \$6 mm Tank Capacities \$38.20 l/min	Ground clearance	m4	150 mm
Clearance Circle - Front without Bucket b 19 833 mm Clearance Circle - Rear wa1 1097 mm Performances Clearance Circle - Rear Wat 1097 mm Travel speed (unladen) 8.90 km/h Wheels Clear Colspan="2">Clear	Overall length - Less Bucket	12	1905 mm
Clearance Circle - Rear wa1 1097 mm Performances Common Section of Manage of	Clearance Radius - Front with Bucket	b18	1473 mm
PerformancesImage: Company of the part of	Clearance Circle - Front without Bucket	b19	833 mm
Travel speed (untaden) 8.90 km/h Wheels 8.70 x 12 Standard tires 8.70 x 12 Engine 10 Engine brand \$ Namar Engine model 3TINV82A-BPMSR Engine norm \$ Stage V Gross Power 18.10 kW Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source 86 Nm / 2400 rpm Starter 12 V Starter 12 V Standard flow - Auxiliary hydraulics 38.20 l/min Tank capacities 38.20 l/min Fuel tank 29 l	Clearance Circle - Rear	wa1	1097 mm
Wheels Image: Brothers Image: Brothers <td>Performances</td> <td></td> <td></td>	Performances		
Standard tires8.70 x 12Engine64Engine brand9YanmarEngine model3TNV82A-BPMSREngine norm5 tage VGross Power1810 kWNet Power66 Nm / 2400 rpmMax. torque / Engine rotation66 Nm / 2400 rpmPower source12 VBattery voltage12 VStarter12 VHydraulics170 kWStandard flow - Auxiliary hydraulics10 Sa.20 l/minTank capacities10 Sa.20 l/minFuel tank29 l	Travel speed (unladen)		8.90 km/h
Engine Image: Desiration of the properties o	Wheels		
Engine brand Yanmar Engine model 3TNV82A-BPMSR Engine norm Stage V Gross Power 18.10 kW Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics 1,70 kW Standard flow - Auxiliary hydraulics 38.20 l/min Tank capacities 1,20 l Fuel tank 29 l	Standard tires		8.70 x 12
Engine model 3TNV82A-BPMSR Engine norm Stage V Gross Power 18.10 kW Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics 38.20 l/min Tank capacities 38.20 l/min Fuel tank 29 l	Engine		
Engine norm Stage V Gross Power 18.10 kW Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics 38.20 l/min Tank capacities 38.20 l/min Fuel tank 29 l	Engine brand		Yanmar
Gross Power 18.10 kW Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics 38.20 l/min Tank capacities 38.20 l/min Fuel tank 29 l	Engine model		3TNV82A-BPMSR
Net Power 17.90 kW Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics ————————————————————————————————————	Engine norm		Stage V
Max. torque / Engine rotation 86 Nm / 2400 rpm Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics ————————————————————————————————————	Gross Power		18.10 kW
Power source Diesel Battery voltage 12 V Starter 1,70 kW Hydraulics ————————————————————————————————————	Net Power		17.90 kW
Battery voltage 12 V Starter 1,70 kW Hydraulics Company of the property of the	Max. torque / Engine rotation		86 Nm / 2400 rpm
Starter 1,70 kW Hydraulics Standard flow - Auxiliary hydraulics 38.20 l/min Tank capacities Fuel tank 1,70 kW 38.20 l/min 38.20 l/min 29 l	Power source		Diesel
HydraulicsStandard flow - Auxiliary hydraulics38.20 l/minTank capacitiesUse of the part o	Battery voltage		12 V
Standard flow - Auxiliary hydraulics Tank capacities Fuel tank 29 l	Starter		1.70 kW
Tank capacities Fuel tank 29 l	Hydraulics		
Fuel tank 29 l	Standard flow - Auxiliary hydraulics		38.20 l/min
	Tank capacities		
Reservoir Capacity Hydraulics 27.30 l	Fuel tank		29 l
	Reservoir Capacity Hydraulics		27.30 l
Displacement 1.30 t	Displacement		1.30 l





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend