## **SKID LOADERS**



**GEHL**®

|                                         | 1640 E CIEduo | et 9 de mayo de 2024, 3.13.30 0 TC |
|-----------------------------------------|---------------|------------------------------------|
| Capacities                              |               | Métrico                            |
| Rated Operating Capacity                |               | 386 kg                             |
| Unladen weight                          |               | 1352 kg                            |
| Weight and dimensions                   |               |                                    |
| Overall Operating Height - Fully Raised | h27           | 3167 mm                            |
| Height to Hinge Pin – Fully Raised      | h28           | 2438 mm                            |
| Overall Height to top of ROPS           | h17           | 1897 mm                            |
| Dump angle at full height               | a5            | 46 °                               |
| Dump height                             | h29           | 1836 mm                            |
| Overall length with bucket              | l16           | 2576 mm                            |
| Dump reach - Full height                | r6            | 376 mm                             |
| Rollback at ground                      | a13           | 30 °                               |
| Seat to ground height                   | h30           | 879 mm                             |
| Wheelbase                               | у             | 775 mm                             |
| Overall width less bucket               | b1            | 909 mm                             |
| Bucket Width                            | e1            | 914 mm                             |
| Ground clearance                        | m4            | 150 mm                             |
| Overall length - Less Bucket            | 12            | 1905 mm                            |
| Clearance Radius - Front with Bucket    | b18           | 1473 mm                            |
| Clearance Circle - Front without Bucket | b19           | 833 mm                             |
| Clearance Circle - Rear                 | wa1           | 1097 mm                            |
| Performances                            |               |                                    |
| Travel speed (unladen)                  |               | 8.90 km/h                          |
| Wheels                                  |               |                                    |
| Standard tires                          |               | 8.70 x 12                          |
| Engine                                  |               |                                    |
| Engine brand                            |               | Yanmar                             |
| Engine model                            |               | 3TNV82A-BPMSR                      |
| Engine norm                             |               | Stage V                            |
| Gross Power                             |               | 18.10 kW                           |
| Net Power                               |               | 17.90 kW                           |
| Max. torque / Engine rotation           |               | 86 Nm / 2400 rpm                   |
| Power source                            |               | Diesel                             |
| Battery voltage                         |               | 12 V                               |
| Starter                                 |               | 1.70 kW                            |
| Hydraulics                              |               |                                    |
| Standard flow - Auxiliary hydraulics    |               | 38.20 l/min                        |
| Tank capacities                         |               |                                    |
| Fueltank                                |               | 29 l                               |
| Reservoir Capacity Hydraulics           |               | 27.30 l                            |
| Displacement                            |               | 1.30 l                             |
|                                         |               |                                    |





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend