Technical sheet :








Capacities		Metric
Rated Operating Capacity		748 kg
Jnladen weight		2792 kg
ipping capacity		1496 kg
Veight and dimensions		1490 Kg
Iverall Operating Height - Fully Raised	h27	3876 mm
leight to Hinge Pin – Fully Raised	h28	3023 mm
Iverall Height to top of ROPS	h17	1948 mm
Sump angle at full height	a5	38 °
ump height	h29	2379 mm
Iverall length with bucket	116	3101 mm
Jump reach - Full height	r6	579 mm
Rollback at ground	a13	28 °
-		20 99 °
Rollback Angle at Full Height	a4	
Seat to ground height	h30	930 mm 988 mm
Vheelbase	У	
Dverall width less bucket	b1	1582 mm
Bucket Width	e1	1562 mm
Sround clearance	m4	160 mm
Overall length - Less Bucket	12	2390 mm
Departure angle	a2	21 °
Clearance Radius - Front with Bucket	b18	1869 mm
Clearance Circle - Front without Bucket	b19	1130 mm
Clearance Circle - Rear	wa1	1466 mm
Performances		
Travel speed (unladen)		12.60 km/h
Wheels		
Standard tires		10X 16.5 - 10 PR HD
Engine		
Engine brand		Yanmar
Engine model		4TNV98-ZNMS3R1
ingine norm		iT4
Gross Power		52.10 kW
Net Power		51.20 kW
Max. torque / Engine rotation		241 Nm / 2500 rpm
Power source		Diesel
Number of cylinders		4
Battery voltage		12 V
Accessory plug		12 V
Alternator - Ampere		100 A
Starter		3 kW
lydraulics		
Standard flow - Auxiliary hydraulics		71.40 l/min
Auxiliary Hydraulic Pressure		207 bar
Fank capacities		
		62.50 I
Fuel tank		
		41.60 l
Hydraulic oil tank capacity		41.60 l 3319 mm ³
Fuel tank Hydraulic oil tank capacity Displacement LH Chain case		

1640R - Dimensional drawing









Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes