Technical sheet:

## **1800R**






	<b>1800R</b> Created on 17 May 2024 at 2:35:01 pm
Capacities	Metric
Rated Operating Capacity	817 kg
Unladen weight	2892 kg
Tipping capacity	1633 kg
Weight and dimensions	
Overall Operating Height - Fully Raised	h27 3876 mm
Height to Hinge Pin – Fully Raised	h28 3023 mm
Overall Height to top of ROPS	h17 1948 mm
Dump angle at full height	a5 38 °
Dump height	h29 2379 mm
Overall length with bucket	l16 3139 mm
Dump reach - Full height	r6 579 mm
Rollback at ground	a13 28 °
Rollback Angle at Full Height	a4 99°
Seat to ground height	h30 930 mm
Wheelbase	y 988 mm
Overall width less bucket	b1 1582 mm
Bucket Width	e1 1562 mm
Ground clearance	m4 160 mm
Overall length - Less Bucket	12 2425 mm
Departure angle	a2 19 °
Clearance Radius - Front with Bucket	b18 1869 mm
Clearance Circle - Front without Bucket	b19 1130 mm
Clearance Circle - Rear	wa1 1519 mm
Performances	
Travel speed (unladen)	12.60 km/h
Wheels	
Standard tires	10X 16.5 - 10 PR HD
Engine	
Engine brand	Yanmar
Engine model	4TNV98-ZNMS3R1
Engine norm	iT4
Gross Power	52.10 kW
Net Power	51.20 kW
Max. torque / Engine rotation	241 Nm / 2500 rpm
Power source	Diesel
Number of cylinders	4
Battery voltage	12 V
Accessory plug	12 V
Alternator - Ampere	100 A
Starter	3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	71.40 l/min
Auxiliary Hydraulic Pressure	207 bar
Tank capacities	207 001
Fuel tank	62.50
Hydraulic oil tank capacity	41.60 l
Displacement	41.00 T
LH Chain case	8.50
RH Chain case	8.50
NI Citalii Case	8.50 1

## 1800R - Dimensional drawing











## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes