SKID LOADERS




GEHL

Rated Operating Capacity Unladen weight Tipping capacity Weight and dimensions Overall Operating Height - Fully Raised Height to Hinge Pin - Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback at ground Rollback Angle at Full Height Wheelbase Overall width less bucket Bucket Width Ground clearance Overall length - Less Bucket	h27 h28 h17 a5 h29 l16 r6 a13 a4 h30 y	Metric 817 kg 2892 kg 1633 kg 3876 mm 3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Unladen weight Tipping capacity Weight and dimensions Overall Operating Height - Fully Raised Height to Hinge Pin - Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h28 h17 a5 h29 l16 r6 a13 a4 h30	2892 kg 1633 kg 3876 mm 3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Tipping capacity Weight and dimensions Overall Operating Height - Fully Raised Height to Hinge Pin – Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h28 h17 a5 h29 l16 r6 a13 a4 h30	1633 kg 3876 mm 3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Weight and dimensions Overall Operating Height - Fully Raised Height to Hinge Pin – Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h28 h17 a5 h29 l16 r6 a13 a4 h30	3876 mm 3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Overall Operating Height - Fully Raised Height to Hinge Pin – Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h28 h17 a5 h29 l16 r6 a13 a4 h30	3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Height to Hinge Pin – Fully Raised Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h28 h17 a5 h29 l16 r6 a13 a4 h30	3023 mm 1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Overall Height to top of ROPS Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h17 a5 h29 l16 r6 a13 a4 h30	1948 mm 38 ° 2379 mm 3139 mm 579 mm 28 ° 99 °
Dump angle at full height Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	a5 h29 l16 r6 a13 a4 h30	38° 2379mm 3139mm 579mm 28° 99° 930mm
Dump height Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h29 l16 r6 a13 a4 h30	2379 mm 3139 mm 579 mm 28° 99° 930 mm
Overall length with bucket Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	l16 r6 a13 a4 h30 y	3139 mm 579 mm 28° 99° 930 mm
Dump reach - Full height Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	r6 a13 a4 h30 y	579 mm 28° 99° 930 mm
Rollback at ground Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	a13 a4 h30 y	28° 99° 930 mm
Rollback Angle at Full Height Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	a4 h30 y	99 ° 930 mm
Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h30 y	930 mm
Seat to ground height Wheelbase Overall width less bucket Bucket Width Ground clearance	h30 y	
Wheelbase Overall width less bucket Bucket Width Ground clearance	•	
Overall width less bucket Bucket Width Ground clearance	•	988 mm
Bucket Width Ground clearance		1582 mm
Ground clearance	e1	1562 mm
	m4	160 mm
o verall tengen Less Buchet	l2	2425 mm
Departure angle	a2	19 °
Clearance Radius - Front with Bucket	b18	1869 mm
Clearance Circle - Front without Bucket	b19	1130 mm
Clearance Circle - Rear	wa1	1519 mm
Performances	wai	1317 111111
Travel speed (unladen)		12.60 km/h
Wheels		12.00 KIII/ II
Standard tires		10X 16.5 - 10 PR HD
Engine		10/10:5 10 11/11/11/
Engine brand		Yanmar
Engine model		4TNV98-ZNMS3R1
Engine norm		iT4, Stage IIIA
Gross Power		52.10 kW
Net Power		52.10 kW
Max. torque / Engine rotation		241 Nm / 2500 rpm Diesel
Power source		
Number of cylinders		4
Battery voltage		12 V
Accessory plug		12 V
Alternator - Ampere		100 A
Starter		3 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		71.40 l/min
Auxiliary Hydraulic Pressure		207 bar
High-Flow Auxiliary Hydraulics – Option		114 l/min
Tank capacities		
Fuel tank		62.50 l
Hydraulic oil tank capacity		41.60 l
Displacement		3.30 l
LH Chain case		8.50 l
RH Chain case		8.50 l

R180 - Dimensional drawing











Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend