SKID LOADERS




GEHL

Capacities		Metric
Rated Operating Capacity		817 kg
Unladen weight		2892 kg
Tipping capacity		1633 kg
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	3876 mm
Height to Hinge Pin – Fully Raised	h28	3023 mm
Overall Height to top of ROPS	h17	1948 mm
Dump angle at full height	a5	38 °
Dump height	h29	2379 mm
Overall length with bucket	l16	3139 mm
Dump reach - Full height	r6	579 mm
Rollback at ground	a13	28 °
Rollback Angle at Full Height	a4	99 °
Seat to ground height	h30	930 mm
Wheelbase	У	988 mm
Overall width less bucket	b1	1582 mm
Bucket Width	e1	1562 mm
Ground clearance	m4	160 mm
Overall length - Less Bucket	12	2425 mm
Departure angle	a2	19 °
Clearance Radius - Front with Bucket	b18	1869 mm
Clearance Circle - Front without Bucket	b19	1130 mm
Clearance Circle - Front without bucket	wa1	1519 mm
Performances	Wai	וווווו פוכו
Travel speed (unladen)		12.60 km/h
Wheels		12.60 KIII/II
Standard tires		10X 16.5 - 10 PR HD
Engine		10A 10.5 - 10 FK 11D
Engine brand		Yanmar
•		4TNV98-ZNMS3R1
Engine model		
For all and a second		
•		iT4, Stage IIIA
Gross Power		iT4, Stage IIIA 52.10 kW
Gross Power Net Power		iT4, Stage IIIA 52.10 kW 51.20 kW
Gross Power Net Power Max. torque / Engine rotation		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm
Gross Power Net Power Max. torque / Engine rotation Power source		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A
Engine norm Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure High-Flow Auxiliary Hydraulics – Option		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure High-Flow Auxiliary Hydraulics – Option Tank capacities		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure High-Flow Auxiliary Hydraulics – Option Tank capacities Fuel tank		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar 114 l/min
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere Starter Hydraulics Standard flow - Auxiliary hydraulics Auxiliary Hydraulic Pressure High-Flow Auxiliary Hydraulics – Option Tank capacities Fuel tank Reservoir Capacity Hydraulics		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar 114 l/min
Gross Power Net Power Max. torque / Engine rotation Power source Number of cylinders Battery voltage Accessory plug Alternator - Ampere		iT4, Stage IIIA 52.10 kW 51.20 kW 241 Nm / 2500 rpm Diesel 4 12 V 12 V 100 A 3 kW 71.40 l/min 207 bar 114 l/min 62.50 l 41.60 l

R180 - Dimensional drawing











Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend