

# AL550

## ARTICULATED LOADERS



### Key Features

- ✓ 4-Post Open Canopy ROPS and FOPS Certified
- ✓ Proportional Auxiliary Hydraulics with Case Drain\* and Circuit Pressure Dump
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Differential Lock (Hydraulically Activated Front and Rear)
- ✓ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ✓ Lift Arm with Z-Bar Kinematics Return to Dig and Mechanical Self-Level
- ✓ Lift Arm Float Detent
- ✓ Hydraglide™ Ride Control\*
- ✓ High-Flow Auxiliary Hydraulics\*

\*Optional features

### Key Specifications

- ✓ 4,830 lbs (2190 kg) Static Tipping Load with Bucket Straight
- ✓ 60 hp (44.7 kW) gross power @ 2300 rpm
- ✓ 91.06" (2.31 m) height to top of ROPS
- ✓ 124.45" (3.16 m) height to hinge pin fully raised
- ✓ 126.18" (3.21 m) outer turning radius

## SPECIFICATIONS

		IMPERIAL
Capacities	Static tipping load with bucket (straight)	4828 lb
	Static tipping load with bucket (full turn)	3732 lb
	Static tipping load with forks (straight)	3411 lb
	Static tipping load with forks (full turn)	2654 lb
	Max. height of bucket pivot point	10 ft 4 in
	Max. lifting height (below forks)	1 ft 5 in
	Breakout force with bucket	4329 daN
Weight and dimensions	Unladen weight (with forks) with 4-post canopy	7470 lb
	Wheelbase	5 ft 9 in
	Overall width of 4 posts canopy	4 ft
	Overall cab width	4 ft
	Overall height with 4 posts canopy	7 ft 7 in
	Overall height with cab	7 ft 7 in
	Tilt-up angle	39.90 °
	Tilt-down angle	44.70 °
	External turning radius (over tyres)	10 ft 6 in
	Articulation angle	45 °
	Overall width less bucket	4 ft 10 in
	Overall length - Less Bucket	13 ft 3 in
	Ground clearance	10 in
	Engine	Engine brand
Engine model		TD 2.2 L3
Engine norm		Stage V / Tier 4 F Final
Number of cylinders / Capacity of cylinders		3 - 21 in <sup>3</sup>
I.C. Engine power rating / Power		60 Hp / 45.50 kW
Max. torque / Engine rotation		148 ft/lbs / 2400 rpm
Engine cooling system		2 radiators water + hydraulic oil
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	18 mph
	Differential lock	Front and rear locking of the machine
Hydraulics	Parking brake	Manual
	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	15 US gpm / 3046 PSI
	High-Flow Option (l/min)	19 US gpm
	Drive hydraulic system pressure	6092 PSI
Tank capacities	Hydraulic oil	12 US gal
	Fuel tank	22 US gal
Miscellaneous	Safety cab homologation	ROPS - FOPS cab (level 1)



## STANDARD FEATURES

- Z-Bar Loader Linkage w/ Limited Self-Leveling
- Inching Pedal
- Lift Tilt Electronic Lockout Switch
- Adjustable and telescopic steering column
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Removable Rubber Floormat
- Tilt & Lift Arm Float Detent with Detent Disable
- Two-Speed Hydrostatic Drive System
- Power-A-Tach® Attachment Mounting System
- Reverse and Brake Tail Lights
- Differential Lock
- Articulation Locking Bar
- Front and Rear - Work Lights
- Canopy
- 12Volt Power Port
- Horn
- Adjustable Seat 5-Way
- Cup Holder

## OPTIONAL FEATURES

- Adaptive air suspension cloth-covered seat with heating and electric lumbar adjustment
- Back-Up Alarm
- Rotating Beacon
- Lockable Storage Box
- Speed control
- 12Volt Power Port
- Rear Auxiliary Hydraulics
- LED Work Lights
- Cabin with Heat
- Hydraglide™ Ride Control
- Strobe Light
- Additional Set of Front Auxiliary Hydraulics

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT