

# V210

## COMPACT LOADERS

**GEHL**®



### KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2032 mm (80")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 249 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3061 mm (120.5") height to hinge pin
- ✓ 1623 mm (63.9") machine width - less bucket
- ✓ 3393 kg (7,480 lbs.) operating weight

		METRIC	IMPERIAL
CAPACITIES	Operating Capacity At 50% Tipping Load	952.54 kg	2100 lb
	Operating Weight	3393 kg	7480 lb
	Unladen weight	3055 kg	6735 lb
	Tipping capacity	1905 kg	4200 lb
WEIGHT AND DIMENSIONS	Wheelbase	1092 mm	43 in
	Overall Operating Height - Fully Raised	4059 mm	160 in
	Height to Hinge Pin - Fully Raised	3061 mm	121 in
	Overall Height to top of ROPS	2032 mm	80 in
	Dump angle at full height	42 °	
	Dump height	2286 mm	90 in
	Overall length with bucket	3543 mm	139 in
	Dump reach - Full height	851 mm	34 in
	Rollback Angle at Full Height	92 °	
	Seat to ground height	952.50 mm	37 in
	Overall width less bucket	1623 mm	64 in
	Ground clearance	178 mm	7 in
	Overall length - Less Bucket	2743 mm	108 in
	Clearance Radius - Front with Bucket	2146 mm	84 in
Rear departure angle	25 °		
PERFORMANCES	Travel speed (unladen)	12.10 km/h	8 mph
	Travel Speed with Two-Speed Option - Maximum	18.70 km/h	12 mph
ENGINE	Engine brand	Yanmar	
	Engine model	4TNV98C-NGL	
	Engine norm	Tier 4	
	Max. torque / Engine rotation	241 Nm / 1625 rpm	178 ft/lbs / 1625 rpm
	Power source	Diesel	
	Number of cylinders	4	
	Engine power (Hp / kW)	70.70 Hp / 51.70 kW	
	Engine cooling system	Water	
	Battery voltage	12 V	
	Alternator - Ampere	100 A	
Starter	3 kW		
HYDRAULICS	Standard flow - Auxiliary hydraulics	86.50 l/min	23 US gpm
	Auxiliary Hydraulic Pressure	239.59 bar	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	114 l/min	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar	3325 PSI
TANK CAPACITIES	Fuel	106 l	28 US gal
	Hydraulic tank capacity	22.70 l	6 US gal
	Displacement	3.30 l	0.87 US gal

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



## STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls

## OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- LED front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera
- Sliding Side Windows



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT