

# V210

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (50%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2032 mm (80")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 249 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3061 mm (120.5") height to hinge pin
- ✓ 1623 mm (63.9") machine width - less bucket
- ✓ 3393 kg (7,480 lbs.) operating weight

SPECIFICATIONS

IMPERIAL		
Capacities	Operating Capacity At 50% Tipping Load	2100 lb
	Operating Weight	7480 lb
	Tipping capacity	4200 lb
Weight and dimensions	Wheelbase	43 in
	Overall Operating Height - Fully Raised	158 in
	Height to Hinge Pin - Fully Raised	121 in
	Overall Height to top of ROPS	80 in
	Dump angle at full height	42 °
	Dump height	90 in
	Overall length with bucket	139 in
	Dump reach - Full height	34 in
	Rollback Angle at Full Height	92 °
	Seat to ground height	37 in
	Overall width less bucket	64 in
	Ground clearance	7 in
	Overall length - Less Bucket	108 in
	Clearance Radius - Front with Bucket	84 in
	Rear departure angle	25 °
Performances	Travel speed (unladen)	8 mph
	Travel Speed with Two-Speed Option - Maximum	12 mph
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NGL
	Engine norm	Tier 4
	Gross Power	70.70 Hp
	Max. torque / Engine rotation	178 ft/lbs / 1625 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
	Starter	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	23 US gpm
	Auxiliary Hydraulic Pressure	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI
Tank capacities	Fuel tank	28 US gal
	Hydraulic tank capacity	6 US gal
	Displacement	0.87 US gal



STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT