

V210 - NEW

COMPACT LOADERS



Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

Key Specifications

- ✓ Operating Capacity (50%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2032 mm (80")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 249 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3061 mm (120.5") height to hinge pin
- ✓ 1623 mm (63.9") machine width - less bucket
- ✓ 3393 kg (7,480 lbs.) operating weight

SPECIFICATIONS

| | | METRIC |
|--|--|--------------------------------------|
| Capacities | Operating Capacity At 50% Tipping Load | 952.54 kg |
| | Operating Weight | 3393 kg |
| | Tipping capacity | 1905 kg |
| Weight and dimensions | Wheelbase | 1092 mm |
| | Overall Operating Height - Fully Raised | 4013 mm |
| | Height to Hinge Pin - Fully Raised | 3061 mm |
| | Overall Height to top of ROPS | 2032 mm |
| | Dump angle at full height | 42 ° |
| | Dump height | 2286 mm |
| | Overall length with bucket | 3543 mm |
| | Dump reach - Full height | 851 mm |
| | Rollback Angle at Full Height | 92 ° |
| | Seat to ground height | 952.50 mm |
| | Overall width less bucket | 1623 mm |
| | Ground clearance | 178 mm |
| | Overall length - Less Bucket | 2743 mm |
| | Clearance Radius - Front with Bucket | 2146 mm |
| | Rear departure angle | 25 ° |
| Performances | Travel speed (unladen) | 12.10 km/h |
| | Travel Speed with Two-Speed Option - Maximum | 18.70 km/h |
| Engine | Engine brand | Yanmar |
| | Engine model | 4TNV98C-NGL |
| | Engine norm | Tier 4 |
| | Gross Power | 52.70 kW |
| | Net Power | 51.70 kW |
| | Max. torque / Engine rotation | 241 Nm / 1625 rpm |
| | Power source | Diesel |
| | Number of cylinders | 4 |
| | Engine cooling system | Water |
| | Battery voltage | 12 V |
| | Alternator - Ampere | 100 A |
| | Starter | 3 kW |
| | Hydraulics | Standard flow - Auxiliary hydraulics |
| Auxiliary Hydraulic Pressure | | 239.59 bar |
| High-Flow Auxiliary Hydraulics - Option | | 114 l/min |
| High-Flow Auxiliary Hydraulics Pressure - Option | | 229.25 bar |
| Tank capacities | Fuel tank | 106 l |
| | Hydraulic tank capacity | 22.70 l |
| | Displacement | 3.30 l |



STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT