

# V210

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (50%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2032 mm (80")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 249 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3061 mm (120.5") height to hinge pin
- ✓ 1623 mm (63.9") machine width - less bucket
- ✓ 3393 kg (7,480 lbs.) operating weight

## SPECIFICATIONS

		METRIC
Capacities	Operating Capacity At 50% Tipping Load	952.54 kg
	Operating Weight	3393 kg
	Tipping capacity	1905 kg
Weight and dimensions	Wheelbase	1092 mm
	Overall Operating Height - Fully Raised	4013 mm
	Height to Hinge Pin - Fully Raised	3061 mm
	Overall Height to top of ROPS	2032 mm
	Dump angle at full height	42 °
	Dump height	2286 mm
	Overall length with bucket	3543 mm
	Dump reach - Full height	851 mm
	Rollback Angle at Full Height	92 °
	Seat to ground height	952.50 mm
	Overall width less bucket	1623 mm
	Ground clearance	178 mm
	Overall length - Less Bucket	2743 mm
	Clearance Radius - Front with Bucket	2146 mm
	Rear departure angle	25 °
Performances	Travel speed (unladen)	12.10 km/h
	Travel Speed with Two-Speed Option - Maximum	18.70 km/h
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NGL
	Engine norm	Tier 4
	Gross Power	70.70 Hp
	Max. torque / Engine rotation	241 Nm / 1625 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
	Starter	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
Tank capacities	Fuel tank	106 l
	Hydraulic tank capacity	22.70 l
	Displacement	3.30 l



## STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT