

# VT210

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (35%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2045 mm (80.5")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 241 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3073 mm (121") height to hinge pin
- ✓ 1674 mm (65.9") machine width - less bucket
- ✓ 4021 kg (8,865 lbs.) operating weight

## SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Operating Weight	8865 lb	4021 kg
	Unladen weight	8049 lb	3651 kg
	Operating Capacity at 35% Tipping Load	2100 lb	952.54 kg
	Operating Capacity At 50% Tipping Load	3000 lb	1360.77 kg
	Operating capacity at 35% tipping load with counterweight	2200 lb	997.90 kg
Weight and dimensions	Tipping capacity	5999 lb	2721 kg
	Overall Operating Height - Fully Raised	159 in	4026 mm
	Height to Hinge Pin - Fully Raised	121 in	3073 mm
	Dump reach - Full height	36 in	927 mm
	Dump angle at full height	42 °	42 °
	Overall Height to top of ROPS	81 in	2045 mm
	Overall length with bucket	139 in	3543 mm
	Ground clearance	8 in	191 mm
	Overall width less bucket	66 in	1674 mm
Engine	Clearance Radius - Front with Bucket	87 in	2210 mm
	Engine brand	Yanmar	Yanmar
	Engine model	4TNV98C-NGL	4TNV98C-NGL
	Gross Power	69.30 Hp	69.30 Hp
	Max. torque / Engine rotation	178 ft/lbs @ 1625 rpm	241 Nm @ 1625 rpm
Hydraulics	Battery voltage	12 V	12 V
	Alternator - Ampere	100 A	100 A
	Standard flow - Auxiliary hydraulics	23 US gpm	86.50 l/min
	Auxiliary Hydraulic Pressure	3475 PSI	239.59 bar
Tank capacities	High-Flow Auxiliary Hydraulics - Option	30 US gpm	114 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI	229.25 bar
	Hydraulic tank capacity	6 US gal	22.70 l
	Fuel tank	38 US gal	143.80 l
	Displacement / Number of cylinders	0.87 US gal / 4	3.30 l / 4



## STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT