

V230

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3086 mm (121.5") height to hinge pin
- ✓ 1707 mm (67.2") machine width - less bucket
- ✓ 3497 kg (7,710 lbs.) operating weight

		METRIC	IMPERIAL
CAPACITIES	Operating Capacity At 50% Tipping Load	1043.26 kg	2300 lb
	Operating Weight	3515 kg	7749 lb
	Unladen weight	3167 kg	6982 lb
	Tipping capacity	2086.53 kg	4600 lb
WEIGHT AND DIMENSIONS	Wheelbase	1092 mm	43 in
	Overall Operating Height - Fully Raised	4079 mm	161 in
	Height to Hinge Pin - Fully Raised	3099 mm	122 in
	Overall Height to top of ROPS	2058 mm	81 in
	Dump angle at full height	42 °	
	Dump height	2312 mm	91 in
	Overall length with bucket	3589 mm	141 in
	Dump reach - Full height	826 mm	33 in
	Rollback Angle at Full Height	92 °	
	Seat to ground height	978 mm	39 in
	Overall width less bucket	1707 mm	67 in
	Ground clearance	203 mm	8 in
	Overall length - Less Bucket	2789 mm	110 in
	Clearance Radius - Front with Bucket	2171 mm	85 in
PERFORMANCES	Travel speed (unladen)	12.70 km/h	8 mph
	Travel Speed with Two-Speed Option - Maximum	20 km/h	12 mph
ENGINE	Engine brand	Yanmar	
	Engine model	4TNV98CT-XNGL	
	Engine nom	Tier 4	
	Max. torque / Engine rotation	294 Nm / 1800 rpm	217 ft/lbs / 1800 rpm
	Power source	Diesel	
	Number of cylinders	4	
	Engine power (Hp / kW)	71.50 Hp / 52.33 kW	
	Engine cooling system	Water	
	Battery voltage	12 V	
	Alternator - Ampere	100 A	
	Starter	3 kW	
HYDRAULICS	Standard flow - Auxiliary hydraulics	86.50 l/min	23 US gpm
	Auxiliary Hydraulic Pressure	239.59 bar	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	114 l/min	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar	3325 PSI
TANK CAPACITIES	Fuel	106 l	28 US gal
	Hydraulic tank capacity	22.70 l	6 US gal
	Displacement	3.30 l	0.87 US gal
	Cooling liquid	18 l	5 US gal

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- LED Work Lights
- Battery Disconnect
- Cup Holder
- Sound reduction Package
- Back-Up Alarm
- Auxiliary Hydraulics
- 4 point lift
- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Two-Speed Drive
- IdealTrax® automatic track tensioning system
- High-Back Adjustable Seat
- Engine Block Heater
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- Brake Control (Auto / Manual)
- Rear Lights
- Anti-Vandalism Protection
- Horn
- Hand throttle

OPTIONAL FEATURES

- Bluetooth car radio
- Sliding Side Windows
- Suspension Seat - Mechanical
- Inner rear view mirror
- Suspension Seat - Air Ride
- ROPS/FOPS Level II Overhead Guard
- A/C Cabin
- Counterweight
- Auto reversing fan
- Swing-out Cab Door



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT