

# V230

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (50%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3086 mm (121.5") height to hinge pin
- ✓ 1707 mm (67.2") machine width - less bucket
- ✓ 3497 kg (7,710 lbs.) operating weight

## SPECIFICATIONS

		IMPERIAL
Capacities	Operating Capacity At 50% Tipping Load	2300 lb
	Operating Weight	7710 lb
	Tipping capacity	4600 lb
Weight and dimensions	Wheelbase	43 in
	Overall Operating Height - Fully Raised	159 in
	Height to Hinge Pin - Fully Raised	121 in
	Overall Height to top of ROPS	81 in
	Dump angle at full height	42 °
	Dump height	91 in
	Overall length with bucket	141 in
	Dump reach - Full height	33 in
	Rollback Angle at Full Height	92 °
	Seat to ground height	39 in
	Overall width less bucket	67 in
	Ground clearance	8 in
	Overall length - Less Bucket	110 in
	Clearance Radius - Front with Bucket	85 in
Performances	Travel speed (unladen)	8 mph
	Travel Speed with Two-Speed Option - Maximum	12 mph
Engine	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine norm	Tier 4
	Gross Power	72 Hp
	Max. torque / Engine rotation	217 ft/lbs / 1800 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
Starter	3 kW	
Hydraulics	Standard flow - Auxiliary hydraulics	23 US gpm
	Auxiliary Hydraulic Pressure	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI
Tank capacities	Fuel tank	28 US gal
	Hydraulic tank capacity	6 US gal
	Displacement	0.87 US gal
	Liquid cooling tank volume	5 US gal



## STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT