# TH10-55 - NEW CONSTRUCTION TELEHANDLERS





## **Key Features**

- SUPERVIEW cab design for increased line of sight to forks and load
- Simple F-N-R joystick mounted to the seat for ease of use and operator comfort
- digital display with 50 operator aid messages to assist in correct operation
- Auxiliary hydraulics and outriggers are standard
- √ high visibility orange seat belt to verify operator use
- ✓ stability system for machine re-position within restricted range

## **Key Specifications**

- ✓ 10,000 lbs. (4540 kg) maximum lifting capacity
- √ 55' 7" (17 m) maximum lifting height
- ✓ 127 hp (95 kW) Deutz diesel engine

# TH10-55 - NEW CONSTRUCTION TELEHANDLERS

## **SPECIFICATIONS**

		IMPERIAL
	Max. capacity	10000 lb
Capacities	Max. lifting height	55 ft 7 in
	Max. outreach	42 ft 3 in
Weight and dimensions	Overall length to carriage	21 ft
	Overall length (with forks)	25 ft
	Overall width	8 ft 4 in
	Overall height	8 ft 6 in
	Wheelbase	11 ft 6 in
	Ground clearance	1 ft 7 in
	Overall cab width	3 ft 1 in
	Tilt-up angle	34 °
	Tilt-down angle	96 °
	External turning radius	12 ft 9 in
	Overall weight	30300 lb
	Tires type	Pneumatic
	Forks length / width / section	48 in x 5 in x 2 in
	Frame leveling longitudinal +/-	10 °
Performances	Lifting	16 s
	Lowering	11 s
	Extension	18 s
	Retraction	16 s
	Crowd	4 s
	Dump	6 s
Engine	Engine brand	Deutz
	Engine norm	Tier 4 final
	Engine model	TCD 3.6 L4
	Number of cylinders / Capacity of cylinders	4 - 220 in <sup>3</sup>
	I.C. Engine power rating - Power	127 Hp / 95 kW
	Max. torque / Engine rotation	369 ft/lbs @ 2300 rpm
Transmission	Transmission type	Powershift
	Number of gears (forward / reverse)	5/3
	Max. travel speed	20 mph
	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
Hydraulics	Hydraulic pump type	Axial piston
	Hydraulic flow / Pressure	40 US gpm-4000 PSI
Tank capacities	Engine oil	2 US gal
	Hydraulic oil	42 US gal
	Diesel Exhaust fluid (AdBlue® type)	4 US gal
	Fuel tank	38 US gal
oise and vibration	Noise at driving position (LpA)	80 dB
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Controls	lovstick



### STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Boom Tip Lift Hook
- Rear Axle Stabilization
- Wet disc brakes
- Front Outriggers
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Easy Manager
- Multi-Function Display Screen

### **OPTIONAL FEATURES**

- A/C Cabin
- Suspension Seat
- Cabin with Heat
- Work Lights Front and Rear

GEHL

One Gehl Way, West Bend, WI 53095 Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.