

# TH10-55

## CONSTRUCTION TELEHANDLERS



### Key Features

- ✓ SUPERVIEW cab design for increased line of sight to forks and load
- ✓ Simple F-N-R joystick mounted to the seat for ease of use and operator comfort
- ✓ digital display with 50 operator aid messages to assist in correct operation
- ✓ Auxiliary hydraulics and outriggers are standard
- ✓ high visibility orange seat belt to verify operator use
- ✓ stability system for machine re-position within restricted range

### Key Specifications

- ✓ 10,000 lbs. (4540 kg) maximum lifting capacity
- ✓ 55' 7" (17 m) maximum lifting height
- ✓ 127 hp (95 kW) Deutz diesel engine

## SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	10000 lb	4535.92 kg
	Max. lifting height	55 ft 7 in	16.95 m
	Maximum outreach	42 ft 3 in	12.88 m
Weight and dimensions	Overall length to carriage	21 ft	6.40 m
	Overall length (with forks)	25 ft	7.62 m
	Overall width	8 ft 4 in	2.54 m
	Overall height	8 ft 6 in	2.59 m
	Wheelbase	11 ft 6 in	3.50 m
	Ground clearance	1 ft 7 in	0.48 m
	Overall cab width	3 ft 1 in	0.95 m
	Tilt-up angle	34 °	34 °
	Tilt-down angle	96 °	96 °
	External turning radius	12 ft 9 in	3.88 m
	Overall weight	30300 lb	13744 kg
	Tires type	Pneumatic	Pneumatic
	Forks length / width / section	48 in x 5 in x 2 in	1219 mm x 127 mm x 50.80 mm
Performances	Frame leveling longitudinal +/-	10 °	10 °
	Lifting	16 s	16 s
	Lowering	11 s	11 s
	Extension	18 s	18 s
	Retraction	16 s	16 s
	Crowd	4 s	4 s
Engine	Dump	6 s	6 s
	Engine brand	Deutz	Deutz
	Engine norm	Tier 4 final	Tier 4 final
	Engine model	TCD 3.6 L4	TCD 3.6 L4
	Number of cylinders / Capacity of cylinders	4 - 220 in³	4 - 3600 cm³
	I.C. Engine power rating - Power	127 Hp / 95 kW	127 Hp / 95 kW
Transmission	Max. torque / Engine rotation	369 ft/lbs @ 2300 rpm	500 Nm @ 2300 rpm
	Transmission type	Powershift	Powershift
	Number of gears (forward / reverse)	5 / 3	5 / 3
	Max. travel speed	20 mph	32 km/h
	Parking brake	Hydraulic spring release SAHR	Hydraulic spring release SAHR
	Service brake	Wet disc brakes	Wet disc brakes
Hydraulics	Hydraulic pump type	Axial piston	Axial piston
	Hydraulic flow / Pressure	40 US gpm-4000 PSI	151 l/min-275.80 bar
Tank capacities	Engine oil	2 US gal	8.51 l
	Hydraulic oil	42 US gal	159 l
	Diesel Exhaust fluid (AdBlue® type)	4 US gal	15.14 l
	Fuel tank	38 US gal	144 l
Noise and vibration	Noise at driving position (LpA)	80 dB	80 dB
Miscellaneous	Steering wheels (front / rear)	2 / 2	2 / 2
	Drive wheels (front / rear)	2 / 2	2 / 2
	Controls	Joystick	Joystick



## STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Boom Tip Lift Hook
- Rear Axle Stabilization
- Wet disc brakes
- Front Outriggers
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Easy Manager
- Multi-Function Display Screen

## OPTIONAL FEATURES

- A/C Cabin
- Suspension Seat
- Cabin with Heat
- Work Lights - Front and Rear

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT