

GEHL®

| Capacities Capacities CASSAS (RESTANDAMENTAL PROPERTY OF THE PROPERTY | Connection | | Motris |
|--|-------------------------------------|---------|----------------------|
| Max. Ditripality in Max. Cutreach 1 5.55 m Weight and dimensions 111 6.40 m Overall length for carriege 111 6.40 m Overall length (with forks) 11 7.52 m Overall length (with forks) 10 2.54 m Overall length (with forks) 10 2.54 m Overall length (with forks) 10 2.54 m Wheelbase y 3.50 m Ground clearance y 3.50 m Overall length (with forks) 5 6.65 m Tik-down angle 4 4 3.4 m Tik-down angle 5 5 9.6 m Tik-down angle 5 16 m 3.38 m Overall weight 16 m 16 m 3.38 m Overall weight 16 m 16 m 3.38 m File stope of the s | • | | |
| Moo. outroach 7.88 m Weight and dimensions 11 6.40 m Overal length to carriage 111 6.40 m Overal length to carriage 111 6.25 m Overal width 51 2.54 m Overal height h77 2.59 m Overal height h77 2.59 m Wheelbase y 3.50 m Ground cleanance m4 0.48 m Till-up angle 35 56 ° Till-up angle 35 56 ° Eternal turning radius Wal 3.28 m Overall weight Wal 3.28 m Till-up angle 44 34 * Till-up angle 45 184 * Eternal turning radius Wal 3.28 m Till-up angle 45 184 * Eternal turning radius Wal 3.28 m Till-s space 18 * 18 * Eternal turning radius 18 * 18 * Till-s space 18 * 18 * Till- | | | - |
| Weight and dimensions 111 6.40 mm Overall length (with forks) 11 7.52 mm Overal length (with forks) 15 2.54 mm Overal height 157 2.59 mm Overal height 157 2.59 mm Wheelbase y 3.30 mm Overall cols with 54 0.95 mm Till-down angle 46 3.44 mm External turning radius Wa3 3.8 mm Overall weight Wa3 3.8 mm Tills down angle 45 19.4 mm External turning radius Wa3 3.8 mm Overall weight 16 fs 19.4 mm Tills down angle 16 fs 19.4 mm Externation 17 e/s 19.4 mm Forks length (width / section 17 e/s 19.5 mm Forks length (width / section 17 e/s 19.5 mm Extensions 17 e/s 19.5 mm 19.5 mm Cowerly 18 mm 19.5 mm 19.5 mm 19.5 mm 19.5 mm 19.5 mm <td< td=""><td></td><td></td><td></td></td<> | | | |
| Overall length for carriage It 7.62 mm Overall length (with forks) bt 2.54 mm Overall length (with forks) bt 2.54 mm Overall length (with forks) bt 2.54 mm Overall length (with forks) bt 2.59 mm Wheelbase y 3.50 mm Ground cleavance y 3.50 mm Overall very with bt 0.55 mm Till-up angle at 3.4° Till-up angle at 3.38 mm Overall weight at 3.73 Mm Till-up angle at 3.38 mm Overall weight at 3.73 Mm Till-up angle at 3.73 Mm Till-up angle at 3.73 Mm Till-up angle at 1.74 Mm Till-up angle at 1. | | | 12.88 m |
| Overall winth for for for for formal the part of the part of the part of formal the p | | | |
| Overall width bit 2.54 m Overall height h7 2.59 m Wheebase y 3.50 m Ground clearance y 3.50 m Owneal clair width bA 0.55 m Date of life-own angle a6 3.4° Edernal turning radius Wa3 3.88 m Overall weight Wa3 3.88 m Overall weight Wa3 3.88 m Tires type Pneumatic 1974 Mg Forks longht width / section [/e/s 1978 Mg Forks longht width / section [/e/s 198 Mg Forks longht width / section [/e/s 198 Mg Bettersion [/e/s 198 Mg 198 Mg Bettersion [/e/s< | | | |
| Overall reight hT/ 2.99 m Wheelbase y 3.50 m Ground clearance m4 0.48 m Overall cab width b4 0.95 m Title-Up angle a4 3.4 m Title-Up angle a5 90 ° External turning radius Wa3 3.88 m Overall weight Wa3 3.88 m Tires type Permeated Permeated Forks length / width / section 1 / e / s 1219 mm x xx m / 50.80 mm Forks length / width / section 1 / e / s 1219 mm x xx m / 50.80 mm Foreigne leveling longitudial -/- 1 / e / s 1219 mm x xx m / 50.80 mm Performance 1 / e / s 1 / e / s 1219 mm x xx m / 50.80 mm Performance 1 / e / s 1 / e / s 1 / e / s Performance 2 / e / s 1 / e / s 1 / e / e Performance 2 / e / e / e / e / e / e 1 / e / e 1 / e / e 1 / e / e 2 / e / e 2 / e / e 2 / e / e 2 / e / e 2 / e / e / e 2 / e / e 2 / e / e | - | | |
| Wheelbase y 3.50 m Counted clarance m4 0.48 m Overall cab width b4 0.95 m Tik-up angle a5 90 ° External turning radius wa3 3.88 m Overall weight Wa3 3.88 m Tires type Peneumatic Forts length, width / section 1 / e /s 1219 mm x27 mm / 50.80 mm Fortice length, width / section 1 / e /s 1219 mm x27 mm / 50.80 mm 70 ° Peneumatic Uniting S 10 mm | | | |
| Ground clearance m4 0.48 m Overall cab width b4 0.95 m Tilk-down angle a4 3.4 m External turning radius Wa3 3.88 m Overall weight Presented 1774 ktg Tires type Prenumatic Prenumatic Forsi length / width / section 1 / e / s 1219 mm x 127 mm / 50.80 mm Farme leveling longitudinal -/- 10° 10° Performance 10° 15° Lifting 10° 15° Lowering 118 18° Extension 18 18° Extension 18 6° Crowd 1 4° Own 4° 5 Engine brand 10° 10° Engine brand | Overall height | h17 | 2.59 m |
| Overall cal width b4 0.95 m Tilt-duanging 36 96° External turning radius Wa3 3.88 m Overall weight Wa3 3.88 m Tiles type 16 /s 1279 mx 127 mm / 50.80 mm Frame leveling longitudinal */- 16 /s 1279 mx 127 mm / 50.80 mm Frame leveling longitudinal */- 16 /s 1279 mx 127 mm / 50.80 mm Frame leveling longitudinal */- 16 /s 1279 mx 127 mm / 50.80 mm Frame leveling longitudinal */- 16 /s 1279 mx 127 mm / 50.80 mm Frame leveling longitudinal */- 16 /s 16 /s Performance 16 /s 17 /s 18 /s Litting 16 /s 18 /s | Wheelbase | у | 3.50 m |
| Tilt-up angle a4 3.6° Tilt-down angle a5 96° External turning radius Wa3 3.88 m Overal weight Wa3 3.88 m Tires type Preumatic 127 mm Forks Length / width / section I / e / s 127 mm 129 mm 127 mm / 50.80 mm Ferdermances Lifting 6 15 12 15 15 15 15 15 15 15 15 15 15 15 15 | Ground clearance | m4 | 0.48 m |
| Tilt-down angle a5 96° External turning radius Wa3 3.88 m Overall weight 1374 kg 1374 kg Peneumatic 1374 kg Peneumatic Peneumatic 1219 mm x 127 mm / 50.80 mm Forks length / With / section 10° 1219 mm x 127 mm / 50.80 mm Formal forks length / With / section 10° 1219 mm x 127 mm / 50.80 mm Formal forks length / With / section 10° | Overall cab width | b4 | 0.95 m |
| External turning radius Wa3 3.88 m Overal tweight 1574 kg 1574 kg Tries type Pneumatic Presented Forks length / width / section 1 e/e /s 279 mm x 127 mm / 50.80 mm Frame leveling longitudinal +/- 10° 10° Performances 11s 11s Lifting 6 s 11s Extension 10° 18 s Retraction 6 s 16 s Crowd 6 s 4 s Dump 6 s Extension Engine brand 16 s Extension Engine brand 16 s Extension Engine norm 10° a.6 t Extension Engine norm 10° a.6 t Extension Max. torque / Engine rotation 4 - 3600 cm² L LC. Engine power ating - Power at | Tilt-up angle | a4 | 34 ° |
| Overall weight 13744 kg Tires type Pneumatic Forks length / width / section 1 / e / s 129 mm x 127 mm / 508 mm Frame leveling longitudinal +/- 10° 10° Performances 1 16 s Lifting 15 mg 118 s Extension 6 18 s Retraction 6 4 s Dump 6 s 4 s Dump 6 s 6 s Engine brand 9 6 s Engine brand 10 mg 100 at Engine norm 10 mg 100 at Engine norm 10 mg 100 at Engine power rating - Power 4 - 3600 cm³ Number of cylinders / Capacity of cylinders 4 - 3600 cm³ LC. Engine power rating - Power 30 kmg 2300 cm³ Nax. torque / Engine rotation 30 kmg 2300 cm³ Transmission 9 9 Name travel speed 5 / 3 Naw. travel Speed 2 9.77 km/h Number of spears (forward / reverse) 5 / 3 < | Tilt-down angle | a5 | 96 ° |
| Overall weight 1374k kg First type Pneumatic Forks length / width / section 1 / e / s 1279 mm x 127 mm / 50.80 mm Frame leveling longitudinal +/- 5 10° Performances 5 18 Lifting 6 115 Lowering 5 185 Extension 6 185 Retraction 6 4 s Crowd 6 4 s Dump 6 5 Engine brand 7 Deutz Engine brand 7 Tier 4 fnal Engine norm 1 Tier 4 fnal Engine norm 7 Tier 4 fnal Engine power rating - Power 7 + Hy 755 kW Max. Graye / Engine rotation 30 km 2300 pm Tansmission 9 Poweshift Number of gears (forward / reverse) 5 / 3 Nax. travel Speed 2 SANR Service brake 9 Axial piston Hydraulic pum type 4 Axial piston <td>External turning radius</td> <td>Wa3</td> <td>3.88 m</td> | External turning radius | Wa3 | 3.88 m |
| Tires type Pneumatic Forks length /width / section 1 / e / s 12 mm x 127 mm / 50.80 mm Frame leveling longitudinal +/- 6 10 ° Performances 6 15 % Lifting 6 15 % Lowering 11 s 18 s Extension 4 36 s Crowd 4 4 s Dump 6 5 Engine 6 4 s Dump 6 5 Engine brand 6 6 5 Engine brand 7 10 mm 1 | | | 13744 kg |
| Forms length / width / section I / e / s 1219 mm x 127 mm / 50.80 mm Frame leveling longitudinal -/- 10° Performances 1 Lifting 6 15 Lowering 115 5 Extension 185 185 Retraction 6 6 6 Crowd 4 5 6 Dump 5 6 5 6 8 6 8 1 6 8 1 6 8 1 | - | | = |
| Frame leveling longitudinal */- 10° Performances 115 Lütting 115 Lowering 115 Extension 18 s Retraction 15 s Crowd 4 s Dump 6 s Engine 6 s Engine brand 16 r4 ral Engine brand 7 iter 4 final Engine model 4 r3000 ral Number of vylinders 4 r3000 ral LC Engine power rating - Power 74 ftp / 5 kW Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission type 9 Powershift Number of gears (forward / reverse) 5 / 3 Nax. travel pase 8 SAHR Service brake 8 Wtt disc brakes Hydraulic pump type 8 Axia piston Hydraulic pump type 5 / 3 Hydraulic flow / Pressure 51 / 3 Engine oil 8 Axia piston Hydraulic oil 5 / 3 Foreign en oil 5 / 3 Hydraulic oil 5 / 3 < | | 1/e/s | |
| Performances 165 s Lifting 16 s Lowering 18 s Extension 18 s Retraction 16 s Crowd 4 s Dump 6 s Engine 6 s Engine brand Deutz Engine norm Tier 4 final Engine nord 7 to 23 s.14 Number of cylinders / Capacity of cylinders 4 - 3600 cm³ LC. Engine power rating - Power 74 th 9/ 5 s.1M Max. toraye / Engine rotation 390 nm @ 2300 rpm Transmission type Powershift Number of gens (froward / reverse) 5 / 3 Max. trayel speed 9 Powershift Number of gens (froward / reverse) 5 / 3 Max. trayel speed 9 Cy7 km/h Parking brake SAHR Service brake 9 Wet disc brakes Hydraulic pump type 5 / 3 Hydraulic pump type 5 / 3 Hydraulic oil 5 / 3 Engine oil 5 / 3 Hydraulic oil 5 / 3 <t< td=""><td></td><td>(, e, s</td><td></td></t<> | | (, e, s | |
| Lifting 16s Lowering 11s Extension 18s Retraction 16s Crowd 6s Dump 6s Engine 6s Engine 10etz Engine brand 10etz Engine more 17er 4 final Engine model 4-3600 cm³ Lc Engine power atting - Power 74 Hp / 5s kW Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission 390 Nm @ 2300 rpm Transmission type 5 / 3 Number of gears (forward / reverse) 5 / 3 Max. travel speed 8 / 29.77 km/h Parking brake 5 / 3 Service brake Wet disc brakes Hydraulic 8 / 44sl piston Hydraulic flow / Pressure 5 / 3 Tank capacities 5 / 3 Engine oil 5 / 3 Hydraulic flow / Pressure 5 / 3 Tank capacities 5 / 3 Flight in the flow of the source 5 / 3 Roll and the flow of | | | 10 |
| Lowering 115 Éxtension 185 Retraction 165 Crowd 45 Dump 65 Engine 65 Engine 10 Engine brand 10 Engine norm 1703.61 4 Number of vylinders / Logacity of cylinders 4-3600 cm³ LC Engine power atting - Power 74 Hp / 55 kW Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission type 9 Number of gears (forward / reverse) 5 / 3 Max. travel speed 9 Parking brake 5 / 3 Service brake 9 Hydraulic pump type 5 / 3 Hydraulic pump type 51 Mini-275.80 bar Hydraulic pump type 51 Mini-275.80 bar Tank capacities 51 Jil min-275.80 bar Engine oil 5.51 Hydraulic jil mighty 5 Jil min-275.80 bar Tank capacities 51 Jil min-275.80 bar Fuglia 55 Jil min-275.80 bar Fuglia 50 Jil min-275.80 bar <td></td> <td></td> <td>16 s</td> | | | 16 s |
| Extension 18s Retraction 16s Crowd 4s Dump 6s Engine | - | | |
| Retraction 16 s Crowd 4 s Dump 6 s Engine ———————————————————————————————————— | - | | |
| Crowd 4 s Dump 6 s Engine ———————————————————————————————————— | | | |
| Dump 6s Engine Company Deuts Engine norm Tier 4 final Tier 4 final Engine model TCD 3.6 L4 TCD 3.6 L4 Number of cylinders / Capacity of cylinders 4 - 3000 cm³ TCD 3.6 L4 Number of generating - Power 390 Nm @ 2300 rpm 390 Nm @ 2300 rpm Max. torque / Engine rotation 390 Nm @ 2300 rpm Temperature Transmission type Powershift 5 / 3 Number of gears (forward / reverse) 5 / 3 SAHR Parking brake SAHR SAHR Service brake 9 Axial piston Hydraulic pump type 5 / 3 Axial piston Engine oil 5 / 3 Axial piston Engine oil 5 / 3 Axial piston Engine oil 5 / 3 Axial piston Hydraulic oil 5 / 3 Axial piston H | | | |
| Engine Common or Design or | | | |
| Engine brand Deutz Engine norm Tier 4 final Engine model TCD 3.6 L4 Number of cylinders / Capacity of cylinders 4 - 3600 cm³ I.C. Engine power rating - Power 74 Hp / 55 kW Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission Powershift Number of gears (forward / reverse) 5 / 3 Max. travel speed Powershift Parking brake SAHR Service brake Wet disc brakes Hydraulic Wet disc brakes Hydraulic pump type Axial piston Hydraulic pump type 51/1 min-275.80 bar Engine oil 8.511 Hydraulic vill 159 l Euet tank 59 l Noise and vibration 8.511 Noise and vibration 8.04B Niscellaneous 8.04B Miscellaneous 2 / 2 Drive wheels (front / rear) 2 / 2 | · | | 6 s |
| Engine norm Tier 4 final Engine model TCD 3.6 L4 Number of cylinders / Capacity of cylinders 4 - 3600 cm³ LC. Engine power rating - Power 974 Hp / 55 kW Max. torque / Engine rotation 390 km @ 2300 rpm Transmission type Powershift Number of gears (forward / reverse) 5 / 3 Max. travel speed 9 797 km /h Parking brake SAHR Service brake 8 Wet disc brakes Hydraulic Wet disc brakes Hydraulic flow / Pressure 51 / 11 / 11 / 11 / 11 / 11 / 11 / 11 / | - | | |
| Engine mode! TCD3.6 L4 Number of cylinders / Capacity of cylinders 4 - 3600 cm³ LC. Engine power rating - Power 390 Nm @ 2300 rpm Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission Powershift Transmission type Powershift Number of gears (forward / reverse) 5 / 3 Max. travel speed SAHR Parking brake Wet disc brakes Hydraulic prake Wet disc brakes Hydraulic pump type 5 / 3 Hydraulic flow / Pressure 151 / min-275.80 bar Tank capacities 5 / 3 Engine oil 8.511 Hydraulic oil \$.515 Fugle acity \$.511 / min-275.80 bar Fugle acity \$.515 / min-275.80 bar Fugle acity | - | | |
| Number of cylinders / Capacity of cylinders 4 - 3600 cm³ LC. Engine power rating - Power 74 Hp / 55 kW Max. torque / Engine rotation 390 Nm @ 2300 rpm Transmission Powershift Transmission type Powershift Number of gears (forward / reverse) 5 / 3 Max. travel speed SAHR Parking brake SAHR Service brake Wet disc brake Hydraulic pump type Axial piston Hydraulic flow / Pressure 151 / min-275.80 bar Engine oil 8.511 Hydraulic oil 5 / 3 Fuel tank 5 / 3 Noise and vibration 5 / 3 Noise and vibration 5 / 3 Noise and vibration (LpA) 8.511 Miscellaneous 9 / 3 Steering wheels (front / rear) 8.0 dB Drive wheels (front / rear) 2 / 2 Drive wheels (front / rear) 2 / 2 | - | | |
| LC Engine power rating - Power74 Hp / 55 kWMax. torque / Engine rotation390 Nm @ 2300 rpmTransmission————————————————————————————————— | - | | |
| Max. torque / Engine rotation390 Nm @ 2300 rpmTransmission9Transmission type5 / 3Number of gears (forward / reverse)5 / 3Max. travel speed92 977 km/hParking brakeSAHRService brake9Hydraulic Plow / Pressure4Hydraulic flow / Pressure4Engine oil8.511 / min-275.80 barHydraulic oil8.511 / min-275.80 barFuel tank9Noise and vibration9Noise and driving position (LpA)80 dBMiscellaneous80 dBSteering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 / 2 | | | |
| TransmissionImage: Comparison typePowershiftNumber of gears (forward / reverse)5 / 3Max. travel speed29.77 km/hParking brakeSAHRService brakeWet disc brakesHydraulic pump typeAxial pistonHydraulic flow / Pressure151 l/min-275.80 barTank capacities151 l/min-275.80 barEngine oil5.51Hydraulic oil5.51Fuel tank159 lFuel to and vibration159 lNoise and vibration (IpA)144 lMiscellaneous8.0 dBMiscellaneous8.0 dBSteering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 | | | |
| Transmission typePowershiftNumber of gears (forward / reverse)5 / 3Max. travel speed29.77 km/hParking brakeSAHRService brakeWet disc brakesHydraulicsWet disc brakesHydraulic pump typeAxial pistonHydraulic flow / Pressure1511/min-275.80 barTank capacites\$8.511Engine oil\$8.511Hydraulic oil\$159 lFuel tank\$6\$4.41Noise and vibration\$6\$8.08Noise at driving position (LpA)\$8.08Miscellaneous\$8.08\$8.08Steering wheels (front / rear)\$6\$8.08 | Max. torque / Engine rotation | | 390 Nm @ 2300 rpm |
| Number of gears (forward / reverse)5 / 3Max. travel speed29.77 km/hParking brakeSAHRService brakeWet disc brakesHydraulicsWet disc brakesHydraulic pump typeAxial pistonHydraulic flow / Pressure151 l/min-275.80 barEngine oil8.51 lHydraulic oil159 lFuel tank159 lNoise and vibration44 lNoise and vibration8.0 dBMiscellaneous8.0 dBSteering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 | Transmission | | |
| Max. travel speed29.77 km/hParking brakeSAHRService brakeWet disc brakesHydraulicsMydraulic pump typeHydraulic flow / Pressure151 l/min-275.80 barTank capacitiesService brakeEngine oil8.51 lHydraulic oil159 lFuel tank159 lNoise and vibration144 lNoise at driving position (LpA)80 dBMiscellaneous80 dBSteering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 | Transmission type | | Powershift |
| Parking brake Service brake Hydraulics Hydraulic pump type Hydraulic flow / Pressure Tank capacities Engine oil Hydraulic oil Fuel tank Noise and vibration Noise and vibration Noise and vibration Steering wheels (front / rear) Drive wheels (front / rear) Finak parking brake Service brake disciplination Service | Number of gears (forward / reverse) | | 5 / 3 |
| Service brakeWet disc brakesHydraulicsHydraulic pump typeAxial pistonHydraulic flow / Pressure151 l/min-275.80 barTank capacitiesService oilService oilHydraulic oil159 lFuel tank159 lNoise and vibration144 lNoise and vibration150 eMiscellaneous150 eSteering wheels (front / rear)150 eDrive wheels (front / rear)2 / 2 | Max. travel speed | | 29.77 km/h |
| HydraulicsMedical pistedHydraulic pump typeAxial pistonHydraulic flow / Pressure151 / min-275.80 barTank capacitiesMedical pistedEngine oil159 lHydraulic oil159 lFuel tank159 lNoise and vibration150Noise at driving position (LpA)159 lMiscellaneous150Steering wheels (front / rear)150Drive wheels (front / rear)150 | Parking brake | | SAHR |
| Hydraulic pump type Hydraulic flow / Pressure Tank capacities Engine oil Hydraulic oil Hydraulic oil Fuel tank Noise and vibration Noise and vibration Noise at driving position (LpA) Miscellaneous Steering wheels (front / rear) Drive wheels (front / rear) Axial piston 151 Maxial piston 152 Maxial piston 153 Maxial piston 154 Maxial piston 155 Maxial piston 155 Maxial piston 155 Maxial piston 154 Maxial piston 155 | Service brake | | Wet disc brakes |
| Hydraulic flow / Pressure 151 l/min-275.80 bar Tank capacities Engine oil Hydraulic oil Hydraulic oil Fuel tank Noise and vibration Noise at driving position (LpA) Miscellaneous Steering wheels (front / rear) Drive wheels (front / rear) | Hydraulics | | |
| Tank capacities Engine oil Hydraulic oil Fuel tank Noise and vibration Noise at driving position (LpA) Miscellaneous Steering wheels (front / rear) Drive wheels (front / rear) Tank capacities B. Stell B. | Hydraulic pump type | | Axial piston |
| Tank capacitiesComparisonEngine oil8.51 lHydraulic oil159 lFuel tank144 lNoise and vibrationComparisonNoise at driving position (LpA)80 dBMiscellaneous80 dBSteering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 | Hydraulic flow / Pressure | | 151 l/min-275.80 bar |
| Engine oil 8.51 l Hydraulic oil 159 l Fuel tank 144 l Noise and vibration Company Noise at driving position (LpA) 80 dB Miscellaneous Company Steering wheels (front / rear) 2 / 2 Drive wheels (front / rear) 2 / 2 | | | |
| Hydraulic oil 159 l Fuel tank 144 l Noise and vibration Noise at driving position (LpA) 80 dB Miscellaneous Steering wheels (front / rear) 2 / 2 Drive wheels (front / rear) 2 / 2 | | | 8.51 l |
| Fuel tank Noise and vibration Noise at driving position (LpA) Miscellaneous Steering wheels (front / rear) Drive wheels (front / rear) 144 l 80 d 80 dB 80 dB 144 l | - | | |
| Noise and vibration80 dBNoise at driving position (LpA)80 dBMiscellaneousUsering wheels (front / rear)Steering wheels (front / rear)2 / 2Drive wheels (front / rear)2 / 2 | | | |
| Noise at driving position (LpA) Miscellaneous Steering wheels (front / rear) Drive wheels (front / rear) 2 / 2 2 / 2 | | | |
| Miscellaneous Steering wheels (front / rear) 2 / 2 Drive wheels (front / rear) 2 / 2 | | | 80 dB |
| Steering wheels (front / rear) 2 / 2 Drive wheels (front / rear) 2 / 2 | | | 00 00 |
| Drive wheels (front / rear) 2 / 2 | | | 2/2 |
| | - | | |
| Controller | Controls | | 2 / 2 Joystick |





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend