## **RS10-55 GEN:4**




## RS10-55 GEN:4 Created on April 18, 2024 at 11:38:58 PM UTC


Capacities		Metric	Imperial
Max. capacity		4535.92 kg	10000 lb
Max. lifting height		16.78 m	55 ft 1 in
Max. outreach		12.55 m	41 ft 2 in
Weight and dimensions			
Length to face of forks	l2	6.40 m	21 ft
Overall width	b1	2.51 m	8 ft 3 in
Overall height	h17	2.59 m	8 ft 6 in
Wheelbase	У	3.15 m	10 ft 4 in
Ground clearance	m4	457.20 mm	18 in
Overall cab width	b4	838 mm	33 in
Tilt-up angle	a4	12 °	12 °
Tilt-down angle	a5	112 °	112 °
External turning radius	Wa3	4.24 m	13 ft 11 in
Unladen weight (with forks)		12610 kg	27800 lb
Overall weight		12609.87 kg	27800 lb
Standard tires		14 x 24	14 x 24
Frame leveling longitudinal +/-		10 °	10 °
Frame leveling corrector	a9	10 °	10 °
Engine			
Engine brand		Deutz	Deutz
Engine norm		Tier 4 final	Tier 4 final
Engine model		TCD 3.6 L4	TCD 3.6 L4
I.C. Engine power rating - Power		120 Hp / 89 kW	120 Hp / 89 kW
Max. torque / Engine rotation		480 Nm @ 1600 rpm	354 ft/lbs @ 1600 rpm
Transmission			
Transmission type		Torque converter with powershift gearbox	Torque converter with powershift gearbox
Number of gears (forward / reverse)		4 / 3	4 / 3
Travel speed (laden)		32.30 km/h	20 mph
Max. travel speed		32.30 km/h	20 mph
Parking brake		SAHR	SAHR
Service brake		Wet disc brakes	Wet disc brakes
Axle Manufacturer		Dana	Dana
Hydraulics			
Hydraulic pump type		Gear pump	Gear pump
Hydraulic flow / Pressure		157.09 l/min-207 bar	41 US gpm-3002 PSI
Tank capacities			
Engine oil		14.70 l	4 US gal
Hydraulic oil		170 l	45 US gal
Fueltank		177.90 l	47 US gal
DEF tank capacity		19 l	5 US gal
Miscellaneous			
Steering wheels (front / rear)		2 / 2	2 / 2
Drive wheels (front / rear)		2 / 2	2 / 2
Safety cab homologation		ROPS/FOPS	ROPS/FOPS
Controls		Single joystick with FNR	Single joystick with FNR

## RS10-55 GEN:4 - Load chart


Machine on tyres with forks Imperial

## Machine on lowered stabilisers with forks Imperial





Α	10,000 lbs. (4536 kg)
В	8,000 lbs. (3629 kg)
С	6,000 lbs. (2722 kg)
D	5,000 lbs. (2268 kg)
E	4,000 lbs. (1814 kg)
F	3,000 lbs. (1361 kg)
G	2,000 lbs. (907 kg)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend