

RS8-44 M74

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ No DEF or DPF needed
- ✓ Simple F-N-R joystick operation
- ✓ 360° operator visibility
- ✓ 4-wheel drive/4-wheel steer

Key Specifications

- ✓ 8,000 lbs. (3629 kg) maximum lifting capacity
- ✓ 44' 0" (13.4 m) maximum lifting height
- ✓ 7,000 lbs. (3176 kg) lift capacity to 44' 0" (13.4 m)
- ✓ 74 hp (55 kW) Deutz diesel engine

SPECIFICATIONS

		METRIC
Capacities	Max. capacity	3628.73 kg
	Max. lifting height	13.41 m
	Max. outreach	9.27 m
Weight and dimensions	Overall length to carriage	6.04 m
	Length to face of forks	5.82 m
	Overall width	2.50 m
	Overall height	2.34 m
	Wheelbase	3.05 m
	Ground clearance	406 mm
	Overall cab width	838 mm
	Tilt-up angle	12 °
	Tilt-down angle	112 °
	External turning radius	4.17 m
	Unladen weight	10660 kg
	Overall weight	10660 kg
	Standard tires	13 x 24
Frame leveling longitudinal +/-	10 °	
Frame leveling corrector	10 °	
Engine	Engine brand	Deutz
	Engine norm	Stage IV / Tier 4 Final
	Engine model	TCD 3.6 L4
	I.C. Engine power rating - Power	74 Hp / 55 kW
	Max. torque / Engine rotation	390 Nm @ 1300 rpm
Transmission	Transmission type	Torque converter with powershift gearbox
	Number of gears (forward / reverse)	4 / 3
	Max. travel speed	24 km/h
	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
	Axle Manufacturer	Dana
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	157 l/min-207 bar
Tank capacities	Hydraulic oil	117.35 l
	Fuel tank	178 l
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Safety cab homologation	ROPS/FOPS
	Controls	Single Joystick FNR



STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Boom Tip Lift Hook
- Rear Axle Stabilization
- Wet disc brakes
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Easy Manager
- Multi-Function Display Screen

OPTIONAL FEATURES

- Suspension Seat
- Light Package - LED
- Rearview Camera
- Solid Rubber Tires
- Rock Tread - Air Foam Tires
- Front Outriggers
- Foam Filled Tires
- PWP System 3-Section Boom
- Enclosed Cab with Heat and A/C

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT