

RS 10-55 M74

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ No DEF or DPF systems
- ✓ Simple F-N-R joystick operation
- ✓ Front outriggers standard for greater forward reach capacity
- ✓ 360° operator visibility

Key Specifications

- ✓ 10,000 lbs. (4536 kg) maximum lifting capacity
- ✓ 55' 1" (16.8 m) maximum lifting height
- ✓ 5,000 lbs. 2268 lift capacity to 55' 1" (16.8 m)
- ✓ 74 hp (55 kW) Deutz diesel engine

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	10000 lb	4535.92 kg
	Max. lifting height	55 ft 1 in	16.78 m
	Maximum outreach	41 ft 2 in	12.55 m
Weight and dimensions	Length to face of forks	21 ft	6.40 m
	Overall width	8 ft 3 in	2.51 m
	Overall height	8 ft 6 in	2.59 m
	Wheelbase	10 ft 4 in	3.15 m
	Ground clearance	18 in	457.20 mm
	Overall cab width	33 in	838 mm
	Tilt-up angle	12 °	12 °
	Tilt-down angle	112 °	112 °
	External turning radius	13 ft 11 in	4.24 m
	Unladen weight (with forks)	27800 lb	12609.87 kg
	Overall weight	27800 lb	12609.87 kg
	Standard tires	14 x 24	14 x 24
	Frame leveling longitudinal +/-	10 °	10 °
	Frame leveling corrector	10 °	10 °
Engine	Engine brand	Deutz	Deutz
	Engine norm	Stage IV, Tier 4 final	Stage IV, Tier 4 final
	Engine model	TCD 3.6 L4	TCD 3.6 L4
	I.C. Engine power rating - Power	74 Hp / 55 kW	74 Hp / 55 kW
	Max. torque / Engine rotation	288 ft/lbs @ 1300 rpm	390 Nm @ 1300 rpm
Transmission	Transmission type	Powershift	Powershift
	Number of gears (forward / reverse)	4 / 3	4 / 3
	Max. travel speed	15 mph	24 km/h
	Parking brake	Hydraulic spring release SAHR	Hydraulic spring release SAHR
	Service brake	Wet disc brakes	Wet disc brakes
	Axle Manufacturer	Dana	Dana
Hydraulics	Hydraulic pump type	Gear pump	Gear pump
	Hydraulic flow / Pressure	41 US gpm-3002 PSI	157.09 l/min-207 bar
Tank capacities	Engine oil	4 US gal	14.70 l
	Hydraulic oil	45 US gal	170 l
	Fuel tank	47 US gal	177.90 l
Miscellaneous	Steering wheels (front / rear)	2 / 2	2 / 2
	Drive wheels (front / rear)	2 / 2	2 / 2
	Cab certification	ROPS/FOPS	ROPS/FOPS
	Controls	Single Joystick FNR	Single Joystick FNR



STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Boom Tip Lift Hook
- Rear Axle Stabilization
- Wet disc brakes
- Front Outriggers
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Easy Manager
- Multi-Function Display Screen

OPTIONAL FEATURES

- Suspension Seat
- Light Package - LED
- Rearview Camera
- Solid Rubber Tires
- Rock Tread - Air Foam Tires
- Foam Filled Tires
- PWP System 4-Section Boom
- Enclosed Cab with Heat and A/C

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT