

# V275

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (50%) - 1247 kg (2,750 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3277 mm (129") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3774 kg (8,320 lbs.) operating weight

## SPECIFICATIONS

		IMPERIAL
Capacities	Operating Capacity At 50% Tipping Load	2750 lb
	Operating Weight	8320 lb
	Tipping capacity	5501 lb
Weight and dimensions	Wheelbase	48 in
	Overall Operating Height - Fully Raised	167 in
	Height to Hinge Pin - Fully Raised	129 in
	Overall Height to top of ROPS	81 in
	Dump angle at full height	42 °
	Dump height	98 in
	Overall length with bucket	150 in
	Dump reach - Full height	33 in
	Rollback Angle at Full Height	92 °
	Seat to ground height	39 in
	Overall width less bucket	67 in
	Ground clearance	9 in
	Overall length - Less Bucket	119 in
	Clearance Radius - Front with Bucket	90 in
	Rear departure angle	30 °
Performances	Travel speed (unladen)	7 mph
	Travel Speed with Two-Speed Option - Maximum	11 mph
Engine	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine norm	Tier 4
	Gross Power	72 Hp
	Max. torque / Engine rotation	217 ft/lbs / 1800 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
	Starter	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	26 US gpm
	Auxiliary Hydraulic Pressure	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	33 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI
Tank capacities	Fuel tank	28 US gal
	Hydraulic tank capacity	6 US gal
	Displacement	0.87 US gal
	Liquid cooling tank volume	5 US gal



## STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT