

# VT275

COMPACT LOADERS



## Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

## Key Specifications

- ✓ Operating Capacity (35%) - 1247 kg (2,750 lbs.)
- ✓ Overall height to top of ROPS - 2082 mm (82")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3289 mm (129.5") height to hinge pin
- ✓ 1803 mm (71") machine width - less bucket
- ✓ 4559 kg (10,051 lbs.) operating weight

## SPECIFICATIONS

	IMPERIAL	
Capacities	Operating Weight	10051 lb
	Operating Capacity at 35% Tipping Load	2750 lb
	Operating Capacity At 50% Tipping Load	3929 lb
Weight and dimensions	Overall Operating Height - Fully Raised	168 in
	Height to Hinge Pin - Fully Raised	129 in
	Dump reach - Full height	35 in
	Dump angle at full height	42 °
	Overall Height to top of ROPS	82 in
	Overall length with bucket	150 in
	Ground clearance	9 in
	Overall width less bucket	71 in
	Bucket Width	74 in
	Clearance Radius - Front with Bucket	93 in
Engine	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Gross Power	53.70 kW
	Net Power	52.70 kW
	Max. torque / Engine rotation	217 ft/lbs @ 1800 rpm
	I.C. Engine power rating	72 Hp
	Battery voltage	12 V
	Alternator - Ampere	100 A
Hydraulics	Standard flow - Auxiliary hydraulics	26 US gpm
	Auxiliary Hydraulic Pressure	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	33 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI
Tank capacities	Hydraulic tank capacity	6 US gal
	Fuel tank	38 US gal
	Liquid cooling tank volume	5 US gal
	Number of cylinders	4



## STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT