

V230 - NEW

KOMPAKTLADER



Wesentliche Merkmale

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

Wichtige Spezifikationen

- ✓ Operating Capacity (50%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3086 mm (121.5") height to hinge pin
- ✓ 1707 mm (67.2") machine width - less bucket
- ✓ 3497 kg (7,710 lbs.) operating weight

SPEZIFIKATIONEN

		METRISCH
Kapazität	Operating Capacity At 50% Tipping Load	1043.26 kg
	Operating Weight	3497 kg
	Tipping capacity	2086.53 kg
Gewicht und Abmessungen	Radstand	1092 mm
	Overall Operating Height - Fully Raised	4039 mm
	Höhe bis Schaufeldrehpunkt – bei max. Hubhöhe	3086 mm
	Overall Height to top of ROPS	2058 mm
	Auskippwinkel bei voller Hubhöhe	42 °
	Dump height	2312 mm
	Overall length with bucket	3589 mm
	Dump reach - Full height	826 mm
	Rückrollwinkel bei voller Hubhöhe	92 °
	Seat to ground height	978 mm
	Overall width less bucket	1707 mm
	Bodenfreiheit der Maschine	203 mm
	Overall length - Less Bucket	2789 mm
	Clearance Radius - Front with Bucket	2171 mm
Leistung	Fahrgeschwindigkeit (unbeladen)	12.70 km/h
	Travel Speed with Two-Speed Option - Maximum	20 km/h
Motor	Marke	Yanmar
	Motor Modell	4TNV98CT-XNGL
	Motornorm	Stage V
	Gross Power	53.70 kW
	Net Power	52.70 kW
	Max. Drehmoment / Motordrehzahl	294 Nm / 1800 rpm
	Antriebsart	Diesel
	Anzahl der Zylinder	4
	Kühlsystem des Motors	Wasser
	Batterie	12 V
	Alternator - Ampere	100 A
	Starter	3 kW
Hydraulisch	Zusatzhydraulik	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
Tankkapazität	Kapazität des Kraftstoffbehälters	106 l
	Kapazität des Hydraulikölbehälters	22.70 l
	Hubraum	3.30 l
	Flüssigkeitskühlung Füllmenge des Behälters	18 l



STANDARDMERKMALE

- 4 point lift
- Rear Lights
- Vandalismusschutz
- Auxiliary Hydraulics
- Hydrostatischer Antrieb - Servo
- Hydraloc™ Sicherheitssystem
- Sound reduction Package
- Rückfahrwarneinrichtung
- Bremssteuerung (Auto / Manuell)
- Heizung für Motorblock
- 12Volt Power Port
- LED Work Lights
- Hupe
- Einzelflansch-Vorder-/Doppelflansch-Hinterleiträder
- Handgas
- Two-Speed Drive
- Cup Holder
- Automatisches Motorabschaltsystem
- Hydraglide™ Ride Control
- Verstellbarer Sitz mit hohem Rücken

OPTIONALE MERKMALE

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Rückspiegel innen
- ROPS/FOPS Schutzdach Stufe II
- Suspension Seat - Air Ride



One Gehl Way, West Bend, WI 53095
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.