

VT210 - NEW

COMPACT LOADERS



Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for more Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

Key Specifications

- ✓ Operating Capacity (35%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2045 mm (80.5")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 241 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3073 mm (121") height to hinge pin
- ✓ 1674 mm (65.9") machine width - less bucket
- ✓ 4021 kg (8,865 lbs.) operating weight

SPEZIFIKATIONEN

		METRISCH
Capacities	Operating Weight	4021 kg
	Unladen weight	3651 kg
	Operating Capacity at 35% Tipping Load	952.54 kg
	Operating Capacity At 50% Tipping Load	1360.77 kg
	Tipping capacity	2721 kg
Weight and dimensions	Overall Operating Height - Fully Raised	4026 mm
	Height to Hinge Pin - Fully Raised	3073 mm
	Dump reach - Full height	927 mm
	Dump angle at full height	42 °
	Overall Height to top of ROPS	2045 mm
	Overall length with bucket	3543 mm
	Ground clearance	191 mm
	Overall width less bucket	1674 mm
	Clearance Radius - Front with Bucket	2210 mm
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NGL
	Gross Power	51.70 kW
	Net Power	51 kW
	Max. torque / Engine rotation	241 Nm @ 1625 rpm
	Battery voltage	12 V
Hydraulics	Alternator - Ampere	100 A
	Standard flow - Auxiliary hydraulics	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
Tank capacities	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
	Hydraulic tank capacity	22.70 l
	Fuel tank	143.80 l
	Displacement / Number of cylinders	3.30 l / 4



STANDARDMERKMALE

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- IdealTrax™ Automatic Track Tensioning System
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control

OPTIONALE MERKMALE

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride



One Gehl Way, West Bend, WI 53095
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.