

VT210 - NEW

TRACK LOADERS



GEHL®

Capacities		Metric	Imperial
Rated Operating Capacity		952.54 kg	2100 lb
Operating Capacity At 50% Tipping Load		1360.77 kg	3000 lb
Rated Operating Capacity with Optional Counterweight		997.90 kg	2200 lb
Operating Weight		4021 kg	8865 lb
Unladen weight		3651 kg	8049 lb
Tipping capacity		2721 kg	5999 lb
Weight and dimensions			
Operating Weight - Approximate		4021 kg	8865 lb
Overall Operating Height - Fully Raised	h27	4026 mm	159 in
Height to Hinge Pin – Fully Raised	h28	3073 mm	121 in
Overall Height to top of ROPS	h17	2045 mm	81 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2300 mm	91 in
Overall length with bucket	l16	3543 mm	139 in
Dump reach - Full height	r6	927 mm	36 in
Rollback Angle at Full Height	a4	92 °	92 °
Seat to ground height	h30	965 mm	38 in
Overall width less bucket	b1	1674 mm	66 in
Ground clearance	m4	191 mm	8 in
Overall length - Less Bucket	l2	2743 mm	108 in
Clearance Radius - Front with Bucket	b18	2210 mm	87 in
Clearance Circle - Rear	wa1	1600 mm	63 in
Performances			
Travel Speed with Two-Speed Option - Maximum		15.30 km/h	10 mph
Travel speed (unladen)		10.30 km/h	6 mph
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98C-NGL	4TNV98C-NGL
Engine norm		Stage V, Tier 4	Stage V, Tier 4
Gross Power		51.70 kW	51.70 kW
Net Power		51 kW	51 kW
Max. torque / Engine rotation		241 Nm / 1625 rpm	178 ft/lbs / 1625 rpm
Number of cylinders		4	4
Engine cooling system		Water	Water
Battery voltage		12 V	12 V
Alternator - Ampere		100 A	100 A
Starter		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		86.50 l/min	23 US gpm
Auxiliary Hydraulic Pressure		239.59 bar	3475 PSI
High-Flow Auxiliary Hydraulics – Option		114 l/min	30 US gpm
High-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar	3325 PSI
Tank capacities			
Fuel tank		143.80 l	38 US gal
Displacement		3.30 l	0.87 US gal



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend