

# VT230 - NEW

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (35%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2045 mm (80.5")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3073 mm (121") height to hinge pin
- ✓ 1753 mm (69") machine width - less bucket
- ✓ 4196 kg (9,250 lbs.) operating weight

## SPEZIFIKATIONEN

|                       |  | METRISCH          |
|-----------------------|--|-------------------|
| Capacities            | Operating Weight                                 | 4196 kg           |
|                       | Operating Capacity at 35% Tipping Load           | 1043.26 kg        |
|                       | Operating Capacity At 50% Tipping Load           | 1490.50 kg        |
| Weight and dimensions | Overall Operating Height - Fully Raised          | 4026 mm           |
|                       | Height to Hinge Pin - Fully Raised               | 3073 mm           |
|                       | Dump reach - Full height                         | 927 mm            |
|                       | Dump angle at full height                        | 42 °              |
|                       | Overall Height to top of ROPS                    | 2045 mm           |
|                       | Overall length with bucket                       | 3589 mm           |
|                       | Ground clearance                                 | 191 mm            |
|                       | Overall width less bucket                        | 1753 mm           |
|                       | Clearance Radius - Front with Bucket             | 2235 mm           |
| Engine                | Engine brand                                     | Yanmar            |
|                       | Engine model                                     | 4TNV98CT-XNGL     |
|                       | Gross Power                                      | 53.70 kW          |
|                       | Net Power  | 52.70 kW          |
|                       | Max. torque / Engine rotation                    | 294 Nm @ 1800 rpm |
|                       | Battery voltage                                  | 12 V              |
|                       | Alternator - Ampere                              | 100 A             |
| Hydraulics            | Standard flow - Auxiliary hydraulics             | 86.50 l/min       |
|                       | Auxiliary Hydraulic Pressure                     | 239.59 bar        |
|                       | High-Flow Auxiliary Hydraulics - Option          | 114 l/min         |
|                       | High-Flow Auxiliary Hydraulics Pressure - Option | 229.25 bar        |
| Tank capacities       | Hydraulic tank capacity                          | 22.70 l           |
|                       | Fuel tank  | 148.80 l          |
|                       | Liquid cooling tank volume                       | 18 l              |
|                       | Displacement / Number of cylinders               | 3.30 l / 4        |



## STANDARDMERKMALE

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONALE MERKMALE

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride



One Gehl Way, West Bend, WI 53095  
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.