

# V275 - NEW

## COMPACT LOADERS



### Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### Key Specifications

- ✓ Operating Capacity (50%) - 1247 kg (2,750 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3277 mm (129") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3774 kg (8,320 lbs.) operating weight

## SPEZIFIKATIONEN

		METRISCH
Capacities	Operating Capacity At 50% Tipping Load	1247.37 kg
	Operating Weight	3774 kg
	Unladen weight	3426 kg
	Tipping capacity	2495 kg
Weight and dimensions	Wheelbase	1219 mm
	Overall Operating Height - Fully Raised	4252 mm
	Height to Hinge Pin - Fully Raised	3277 mm
	Overall Height to top of ROPS	2058 mm
	Dump angle at full height	42 °
	Dump height	2489 mm
	Overall length with bucket	3810 mm
	Dump reach - Full height	830 mm
	Rollback Angle at Full Height	92 °
	Seat to ground height	978 mm
	Overall width less bucket	1712 mm
	Ground clearance	216 mm
	Overall length - Less Bucket	3023 mm
	Clearance Radius - Front with Bucket	2289 mm
	Rear departure angle	30 °
Performances	Travel speed (unladen)	11.40 km/h
	Travel Speed with Two-Speed Option - Maximum	17.50 km/h
Engine	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine norm	Stage V
	Gross Power	53.70 kW
	Net Power	52.70 kW
	Max. torque / Engine rotation	294 Nm / 1800 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
Hydraulics	Standard flow - Auxiliary hydraulics	98.40 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	126 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
Tank capacities	Fuel tank	106 l
	Hydraulic tank capacity	22.70 l
	Displacement	3.30 l
	Liquid cooling tank volume	18 l



## STANDARDMERKMALE

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- High-Back Adjustable Seat

## OPTIONALE MERKMALE

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride



One Gehl Way, West Bend, WI 53095  
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.