

# V275 - NEW

# SKID LOADERS



# GEHL®

| Capacities                                       |     | Imperial              |
|--|-----|-----------------------|
| Operating Capacity At 50% Tipping Load           |     | 2750 lb               |
| Operating Weight                                 |     | 8320 lb               |
| Unladen weight                                   |     | 7553 lb               |
| Tipping capacity                                 |     | 5501 lb               |
| Weight and dimensions                            |     |                       |
| Operating Weight - Approximate                   |     | 8320 lb               |
| Overall Operating Height - Fully Raised          | h27 | 167 in                |
| Height to Hinge Pin - Fully Raised               | h28 | 129 in                |
| Overall Height to top of ROPS                    | h17 | 81 in                 |
| Dump angle at full height                        | a5  | 42 °                  |
| Dump height                                      | h29 | 98 in                 |
| Overall length with bucket                       | l16 | 150 in                |
| Dump reach - Full height                         | r6  | 33 in                 |
| Rollback Angle at Full Height                    | a4  | 92 °                  |
| Seat to ground height                            | h30 | 39 in                 |
| Overall width less bucket                        | b1  | 67 in                 |
| Ground clearance                                 | m4  | 9 in                  |
| Overall length - Less Bucket                     | l2  | 119 in                |
| Clearance Radius - Front with Bucket             | b18 | 90 in                 |
| Clearance Circle - Front without Bucket          | b19 | 56 in                 |
| Clearance Circle - Rear                          | wa1 | 72 in                 |
| Performances                                     |     |                       |
| Travel Speed with Two-Speed Option - Maximum     |     | 11 mph                |
| Travel speed (unladen)                           |     | 7 mph                 |
| Engine   |     |                       |
| Engine brand                                     |     | Yanmar                |
| Engine model                                     |     | 4TNV98CT-XNGL         |
| Engine norm                                      |     | Stage V, Tier 4       |
| Gross Power                                      |     | 53.70 kW              |
| Net Power  |     | 52.70 kW              |
| Max. torque / Engine rotation                    |     | 217 ft/lbs / 1800 rpm |
| Power source                                     |     | Diesel                |
| Number of cylinders                              |     | 4                     |
| Engine cooling system                            |     | Water                 |
| Battery voltage                                  |     | 12 V                  |
| Alternator - Ampere                              |     | 100 A                 |
| Starter  |     | 3 kW                  |
| Hydraulics                                       |     |                       |
| Standard flow - Auxiliary hydraulics             |     | 26 US gpm             |
| Auxiliary Hydraulic Pressure                     |     | 3475 PSI              |
| High-Flow Auxiliary Hydraulics – Option          |     | 33 US gpm             |
| High-Flow Auxiliary Hydraulics Pressure – Option |     | 3325 PSI              |
| Tank capacities                                  |     |                       |
| Fuel tank  |     | 28 US gal             |
| Reservoir Capacity Hydraulics                    |     | 6 US gal              |
| Displacement                                     |     | 0.87 US gal           |
| Coolant system capacity                          |     | 5 US gal              |



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend