

V275 - NEW

SKID LOADERS



GEHL®

| Capacities | | Metric |
|--|-----|-------------------|
| Operating Capacity At 50% Tipping Load | | 1247.37 kg |
| Operating Weight | | 3774 kg |
| Unladen weight | | 3426 kg |
| Tipping capacity | | 2495 kg |
| Weight and dimensions | | |
| Operating Weight - Approximate | | 3774 kg |
| Overall Operating Height - Fully Raised | h27 | 4252 mm |
| Height to Hinge Pin – Fully Raised | h28 | 3277 mm |
| Overall Height to top of ROPS | h17 | 2058 mm |
| Dump angle at full height | a5 | 42 ° |
| Dump height | h29 | 2489 mm |
| Overall length with bucket | l16 | 3810 mm |
| Dump reach - Full height | r6 | 830 mm |
| Rollback Angle at Full Height | a4 | 92 ° |
| Seat to ground height | h30 | 978 mm |
| Overall width less bucket | b1 | 1712 mm |
| Ground clearance | m4 | 216 mm |
| Overall length - Less Bucket | l2 | 3023 mm |
| Clearance Radius - Front with Bucket | b18 | 2289 mm |
| Clearance Circle - Front without Bucket | b19 | 1410 mm |
| Clearance Circle - Rear | wa1 | 1829 mm |
| Performances | | |
| Travel Speed with Two-Speed Option - Maximum | | 17.50 km / h |
| Travel speed (unladen) | | 11.40 km / h |
| Engine | | |
| Engine brand | | Yanmar |
| Engine model | | 4TNV98CT-XNGL |
| Engine norm | | Stage V, Tier 4 |
| Gross Power | | 53.70 kW |
| Net Power | | 52.70 kW |
| Max. torque / Engine rotation | | 294 Nm / 1800 rpm |
| Power source | | Diesel |
| Number of cylinders | | 4 |
| Engine cooling system | | Water |
| Battery voltage | | 12 V |
| Alternator - Ampere | | 100 A |
| Starter | | 3 kW |
| Hydraulics | | |
| Standard flow - Auxiliary hydraulics | | 98.40 l/min |
| Auxiliary Hydraulic Pressure | | 239.59 bar |
| High-Flow Auxiliary Hydraulics – Option | | 126 l/min |
| High-Flow Auxiliary Hydraulics Pressure – Option | | 229.25 bar |
| Tank capacities | | |
| Fuel tank | | 106 l |
| Reservoir Capacity Hydraulics | | 22.70 l |
| Displacement | | 3.30 l |
| Coolant system capacity | | 18 l |



Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend