

VT275

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

KEY SPECIFICATIONS

- ✓ Operating Capacity (35%) - 1247 kg (2,750 lbs.)
- ✓ Overall height to top of ROPS - 2082 mm (82")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3289 mm (129.5") height to hinge pin
- ✓ 1803 mm (71") machine width - less bucket
- ✓ 4559 kg (10,051 lbs.) operating weight

		METRIC	
CAPACITIES	Operating Weight	4649 kg	
	Operating Capacity at 35% Tipping Load	1247.37 kg	
	Operating Capacity At 50% Tipping Load	1782.16 kg	
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	4265 mm	
	Height to Hinge Pin - Fully Raised	3289 mm	
	Dump reach - Full height	879 mm	
	Dump angle at full height	42 °	
	Overall Height to top of ROPS	2082 mm	
	Overall length with bucket	3810 mm	
	Ground clearance	229 mm	
	Overall width less bucket	1803 mm	
	Bucket Width	1880 mm	
ENGINE	Engine brand	Yanmar	
	Engine model	4TNV98CT-XNGL	
	Engine power (Hp)	72.82 Hp	
	Engine power (kW)	53.30 kW	
	Max. torque / Engine rotation	294 Nm @ 1800 rpm	
	Battery voltage	12 V	
	Alternator - Ampere	100 A	
	HYDRAULICS	Standard flow - Auxiliary hydraulics	98.40 l/min
		Auxiliary Hydraulic Pressure	239.59 bar
		High-Flow Auxiliary Hydraulics - Option	126 l/min
High-Flow Auxiliary Hydraulics Pressure - Option		229.25 bar	
TANK CAPACITIES	Hydraulic tank capacity	22.70 l	
	Fuel	143.80 l	
	Cooling liquid	18 l	
	Number of cylinders	4	

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls

OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- led front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera
- Sliding Side Windows



One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT