VT275 - NEW

TRACK LOADERS



GEHL

Capacities		Metric
Rated Operating Capacity		1247.37 kg
Operating Capacity At 50% Tipping Load		1782.16 kg
Rated Operating Capacity with Optional Counterweight		1301.81 kg
Operating Weight		4559 kg
Unladen weight		4145 kg
Weight and dimensions		ga cere
Operating Weight - Approximate		4559 kg
Overall Operating Height - Fully Raised	h27	4265 mm
Height to Hinge Pin – Fully Raised	h28	3289 mm
Overall Height to top of ROPS	h17	2082 mm
Dump angle at full height	a5	42 °
Dump height	h29	42 2502 mm
	1129	3810 mm
Overall length with bucket	r6	3810 mm
Dump reach - Full height		92 °
Rollback Angle at Full Height	a4	
Seat to ground height	h30	1003 mm
Overall width less bucket Bucket Width	b1	1803 mm
	e1	1880 mm
Ground clearance	m4	229 mm
Overall length - Less Bucket	12	3023 mm
Clearance Radius - Front with Bucket	b18	2362 mm
Clearance Circle - Front without Bucket	b19	1486 mm
Clearance Circle - Rear	wa1	1753 mm
Performances Travel Consideration Manipus		13.50 km/h
Travel Speed with Two-Speed Option - Maximum		8.90 km/h
Travel speed (unladen)		8.90 KIII/II
Engine		Yanmar
Engine brand		4TNV98CT-XNGL
Engine model Engine norm		
Gross Power		Stage V, Tier 4 53.70 kW
Net Power		53.70 kW 52.70 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm Diesel
Power source		Dieset 4
Number of cylinders		
Engine cooling system		Water 12 V
Battery voltage		
Alternator - Ampere		100 A
Starter		3 kW
Hydraulics		00 / 0 1 /
Standard flow - Auxiliary hydraulics		98.40 l/min
Auxiliary Hydraulic Pressure		239.59 bar
High-Flow Auxiliary Hydraulics - Option		126 l/min
High-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar
Tank capacities		
Fuel tank		143.80 l
Reservoir Capacity Hydraulics		22.70 l
Coolant system capacity		18 l





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend