SKID LOADERS



GEHL®

Capacities	Métrico	
Operating Capacity At 50% Tipping Load	861.82 kg	
Operating Weight	3172.87 kg	
Veight and dimensions		
Overall Operating Height - Fully Raised	h27 3886.20 mm	
leight to Hinge Pin – Fully Raised	h28 3022.60 mm	
Overall Height to top of ROPS	h17 1955.80 mm	
Dump angle at full height	a5 38 °	
Dump height	h29 2387.60 mm	
Overall length with bucket	l16 3251.20 mm	
Dump reach - Full height	r6 584.20 mm	
Rollback at ground	a13 28 °	
Rollback Angle at Full Height	a4 99 °	
Seat to ground height	h30 904.24 mm	
Wheelbase	y 1066.80 mm	
Overall width less bucket	b1 1574.80 mm	
Bucket Width	e1 1676.40 mm	
Ground clearance	m4 160.02 mm	
Overall length - Less Bucket	12 2446.02 mm	
Clearance Radius - Front with Bucket	b18 2032 mm	
Clearance Circle - Front without Bucket	b19 1168.40 mm	
Clearance Circle - Rear	wa1 1511.30 mm	
Performances	wai 1511.50 iiiiii	
Fravel Speed with Two-Speed Option - Maximum	19.47 km/h	
Fravel speed (unladen)	12.55 km/h	
Wheels	12,55 KIII/II	
Standard tires	10 x 16.5	
Engine	10 X 10.3	
•	Yanmar	
Engine brand	4TNV98C-NMS2V	
Engine model		r:
Engine norm	Stage IIIB, Stage IV / Tier 4	Final
Gross Power	51.67 kW	
Net Power	51 kW	
Max. torque / Engine rotation	241 Nm / 1625 rpm	
Power source	Diesel	
.C. Engine power rating	69.30 Hp	
Battery voltage	12 V	
Starter	3 kW	
Hydraulics		
Standard flow - Auxiliary hydraulics	70.78 l/min	
Auxiliary Hydraulic Pressure	207 bar	
ligh-Flow Auxiliary Hydraulics – Option	113.94 l/min	
ligh-Flow Auxiliary Hydraulics Pressure – Option	200 bar	
Tank capacities		
Fuel tank	58.67 l	
lydraulic oil tank capacity	35.96 l	
Noise and vibration		
Noise to environment (LwA)	100 dB	
Vhole-Body Vibration (ISO 2631-1)	0.96 m/s ²	
Vibration on hands/arms	< 1.53 m/s ²	





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend