

R190 GEN:2

COMPACT LOADERS



Key Features

- ✓ All-Tach® Attachment System (Universal Type)
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar or Joystick Control System
- ✓ Zero Maintenance Axles w/8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner
- ✓ Standard High Back Cushion Seat

Key Specifications

- ✓ Operating capacity (50%) - 862 kg (1,900 lbs.)
- ✓ Overall height to top of ROPS - 1956 mm (77")
- ✓ Gross Power - 69.3 hp (51.67 kW) @ 1625 rpm
- ✓ Yanmar / 4TNV98C-NMS2V / Tier IV
- ✓ 241 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3022 mm (119") height to hinge pin
- ✓ 1575 mm (62") machine width - less bucket
- ✓ 3173 kg (6,995 lbs.) operating weight

ESPECIFICACIONES

		MÉTRICO
Capacities	Operating Capacity At 50% Tipping Load	861.82 kg
	Operating Weight	3172.87 kg
	Tipping capacity	1723.65 kg
Weight and dimensions	Wheelbase	1066.80 mm
	Overall Operating Height - Fully Raised	3886.20 mm
	Height to Hinge Pin - Fully Raised	3022.60 mm
	Overall Height to top of ROPS	1955.80 mm
	Dump angle at full height	38 °
	Dump height	2387.60 mm
	Overall length with bucket	3251.20 mm
	Dump reach - Full height	584.20 mm
	Rollback at ground	28 °
	Rollback Angle at Full Height	99 °
	Seat to ground height	904.24 mm
	Overall width less bucket	1574.80 mm
	Bucket Width	1676.40 mm
	Ground clearance	160.02 mm
	Overall length - Less Bucket	2446.02 mm
	Clearance Radius - Front with Bucket	2032 mm
Rear departure angle	21 °	
Performances	Travel speed (unladen)	12.55 km/h
	Travel Speed with Two-Speed Option - Maximum	19.47 km/h
Wheels	Standard tires	10 x 16.5
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Engine norm	Stage IIIA
	Gross Power	51.67 kW
	Net Power	51 kW
	Max. torque / Engine rotation	241 Nm / 1625 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	3 kW
	Hydraulics	Standard flow - Auxiliary hydraulics
Auxiliary Hydraulic Pressure		207 bar
High-Flow Auxiliary Hydraulics - Option		113.94 l/min
High-Flow Auxiliary Hydraulics Pressure - Option		200 bar
Tank capacities	Fuel tank	58.67 l
	Hydraulic tank capacity	35.96 l
Noise and vibration	Noise to environment (LwA)	100 dB
	Whole-Body Vibration (ISO 2631-1)	0.96 m/s ²
	Vibration on hands/arms	< 1.53 m/s ²



CARACTERÍSTICAS DE SERIE

- T-Bar Controls
- High-Back Adjustable Seat
- Sound Reduction Material
- Hydrostatic Drive - Servo
- Adjustable 2-inch Seat Belt
- Hydraloc™ Safety System
- Anti-Vandalism Lock Provisions
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- 12Volt Power Port
- Horn
- Fuel gauge with low level indicator
- Pilot Joystick Controls

CARACTERÍSTICAS OPCIONALES

- Suspension Seat
- Selectable Self-Leveling Hydraulic Lift Action 4
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Ceiling light
- Back-Up Alarm
- Inner rear view mirror
- Rotating Beacon
- LED Work Lights
- Heat & Defrost
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- Engine Block Heater
- 3-inch Seatbelt
- Bluetooth car radio
- Swing-out Cab Door
- Simplified lifting system without spreader bar



One Gehl Way, West Bend, WI 53095
Teléfono: (262) 334-9461



GEHL COMPACT EQUIPMENT

® Representa registro en los Estados Unidos. Las marcas comerciales pueden o no estar registradas en otros países.