

RT195 - NEW

COMPACT LOADERS



Key Features

- ✓ Multiple Track Widths and Tread Patterns
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Pilot Operated Joystick Controls
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-Out Cooler

Key Specifications

- ✓ 2,787 lbs. (1264 kg) Rated Operating Capacity (50%)
- ✓ 69.3 hp (51.7 kW) Yanmar Engine 4TNV98C-NMS2, Stage IV
- ✓ 120" (3048 mm) Height to Hinge Pin
- ✓ 69" (1749 mm) Overall Machine Width Less Bucket
- ✓ 78" (1979 mm) Overall Height to top of ROPS

SPECIFICATIONS

		METRIC
Capacities	Rated Operating Capacity	885 kg
	Rated Operating Capacity with Optional Counterweight	929,86 kg
	Operating Weight	3697 kg
	Unladen weight	3422 kg
	Operating Capacity At 50% Tipping Load	1264 kg
Weight and dimensions	Tipping capacity	2527 kg
	Overall Operating Height - Fully Raised	4018 mm
	Height to Hinge Pin - Fully Raised	3048 mm
	Dump reach - Full height	648 mm
	Dump angle at full height	39 °
	Overall length with bucket	3279 mm
	Departure angle	27 °
	Ground clearance	188 mm
	Overall width less bucket	1746 mm
	Bucket Width	1778 mm
Clearance Radius - Front with Bucket	2063 mm	
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Gross Power	51.70 kW
	Net Power	51 kW
	Max. torque / Engine rotation	241 Nm @ 2500 rpm
	I.C. Engine power rating - Power	68.40 Hp / 51 kW
	Battery voltage	12 V
	Accessory plug	120 V
	Alternator - Ampere	100 A
Transmission	Transmission type	Hydrostatic
Hydraulics	Standard flow - Auxiliary hydraulics	71 l/min
	Auxiliary Hydraulic Pressure	380 bar
	High-Flow Auxiliary Hydraulics - Option	113 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	420 bar
Tank capacities	Hydraulic tank capacity	36 l
	Fuel tank	58,70 l
	Liquid cooling tank volume	12,90 l
Noise and vibration	Displacement / Number of cylinders	3,30 l / 4
	Noise to environment (LwA)	101,40 dB
	Noise at driving position (LpA)	82 dB
	Whole-Body Vibration (ISO 2631-1)	1,10 m/s ²



STANDARD FEATURES

- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydraloc™ Safety System
- Brake Control (Auto / Manual)
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- Hydrostatic Drive - Servo
- 12Volt Power Port
- Horn
- Two-Speed Drive
- Cup Holder
- High-Back Adjustable Seat
- Integral Access Plate (removable)
- Pilot Joystick Controls
- Lift Arm Support Device
- All-Tach® Attachment Mounting System
- Operator Restraint Bar
- IdealTrax® automatic track tensioning system

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Cab Enclosure
- Suspension Seat - Mechanical
- Back-Up Alarm
- Engine Block Heater
- Cabin with Heat
- Hydraglide™ Ride Control
- Air Ride Suspension Seat
- High-Flow Auxiliary Hydraulics
- Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT