

RT195 - NEW

COMPACT LOADERS



Key Features

- ✓ Multiple Track Widths and Tread Patterns
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Pilot Operated Joystick Controls
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-Out Cooler

Key Specifications

- ✓ 2,787 lbs. (1264 kg) Rated Operating Capacity (50%)
- ✓ 69.3 hp (51.7 kW) Yanmar Engine 4TNV98C-NMS2, Stage IV
- ✓ 120" (3048 mm) Height to Hinge Pin
- ✓ 69" (1749 mm) Overall Machine Width Less Bucket
- ✓ 78" (1979 mm) Overall Height to top of ROPS

SPECIFICATIONS

IMPERIAL		
Capacities	Operating Weight	8150 lb
	Unladen weight	7544 lb
	Operating Capacity at 35% Tipping Load	1950 lb
	Operating Capacity At 50% Tipping Load	2787 lb
	Operating capacity at 35% tipping load with counterweight	2050 lb
	Tipping capacity	5571 lb
Weight and dimensions	Overall Operating Height - Fully Raised	158 in
	Height to Hinge Pin - Fully Raised	120 in
	Dump reach - Full height	26 in
	Dump angle at full height	39 °
	Overall length with bucket	129 in
	Departure angle	27 °
	Ground clearance	7 in
	Overall width less bucket	69 in
	Bucket Width	70 in
	Clearance Radius - Front with Bucket	81 in
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Gross Power	68.40 Hp
	Max. torque / Engine rotation	178 ft/lbs @ 2500 rpm
	Power	51 kW
	Battery voltage	12 V
	Accessory plug	120 V
	Alternator - Ampere	100 A
Transmission	Transmission type	Hydrostatic
Hydraulics	Standard flow - Auxiliary hydraulics	19 US gpm
	Auxiliary Hydraulic Pressure	5511 PSI
	High-Flow Auxiliary Hydraulics - Option	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	6092 PSI
Tank capacities	Hydraulic tank capacity	10 US gal
	Fuel tank	16 US gal
	Liquid cooling tank volume	3 US gal
	Displacement / Number of cylinders	0.87 US gal / 4
Noise and vibration	Noise to environment (LWA)	101.40 dB
	Noise at driving position (LpA)	82 dB
	Whole-Body Vibration (ISO 2631-1)	1.10 m/s²



STANDARD FEATURES

- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydraloc™ Safety System
- Brake Control (Auto / Manual)
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- Hydrostatic Drive - Servo
- 12Volt Power Port
- Horn
- Two-Speed Drive
- Cup Holder
- High-Back Adjustable Seat
- Integral Access Plate (removable)
- Pilot Joystick Controls
- Lift Arm Support Device
- All-Tach® Attachment Mounting System
- Operator Restraint Bar
- IdealTrax® automatic track tensioning system

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Cab Enclosure
- Suspension Seat - Mechanical
- Back-Up Alarm
- Engine Block Heater
- Cabin with Heat
- Hydraglide™ Ride Control
- Air Ride Suspension Seat
- High-Flow Auxiliary Hydraulics
- Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT