

RT195 - NEW

COMPACT LOADERS



Key Features

- ✓ Multiple Track Widths and Tread Patterns
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Pilot Operated Joystick Controls
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-out Cooler

Key Specifications

- ✓ 2,787 lbs. (1264 kg) Rated Operating Capacity (50%)
- ✓ 69.3 hp (51.7 kW) Yanmar Engine 4TNV98C-NMS2, Stage IV
- ✓ 120" (3048 mm) Height to Hinge Pin
- ✓ 69" (1749 mm) Overall Machine Width Less Bucket
- ✓ 78" (1979 mm) Overall Height to top of ROPS

SPEZIFIKATIONEN

		METRISCH
Capacities	Rated Operating Capacity	885 kg
	Operating Weight	3697 kg
	Unladen weight	3422 kg
	Operating Capacity At 50% Tipping Load	1264 kg
	Tipping capacity	2527 kg
Weight and dimensions	Overall Operating Height - Fully Raised	4018 mm
	Height to Hinge Pin - Fully Raised	3048 mm
	Dump reach - Full height	648 mm
	Dump angle at full height	39 °
	Overall length with bucket	3279 mm
	Departure angle	27 °
	Ground clearance	188 mm
	Overall width less bucket	1746 mm
	Bucket Width	1778 mm
	Clearance Radius - Front with Bucket	2063 mm
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Gross Power	51.70 kW
	Net Power	51 kW
	Max. torque / Engine rotation	241 Nm @ 2500 rpm
	I.C. Engine power rating - Power	68.40 Hp / 51 kW
	Battery voltage	12 V
	Accessory plug	120 V
	Alternator - Ampere	100 A
Transmission	Transmission type	Hydrostatic
Hydraulics	Standard flow - Auxiliary hydraulics	71 l/min
	Auxiliary Hydraulic Pressure	380 bar
	High-Flow Auxiliary Hydraulics - Option	113 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	420 bar
Tank capacities	Hydraulic tank capacity	36 l
	Fuel tank	58.70 l
	Liquid cooling tank volume	12.90 l
	Displacement / Number of cylinders	3.30 l / 4
Noise and vibration	Noise to environment (LwA)	101.40 dB
	Noise at driving position (LpA)	82 dB
	Whole-Body Vibration (ISO 2631-1)	1.10 m/s²



STANDARDMERKMALE

- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydraloc™ Safety System
- Brake Control (Auto / Manual)
- ROPS/FOPS Level II Overhead Guard
- Front and Rear - Work Lights
- Hydrostatic Drive - Servo
- 12Volt Power Port
- Horn
- Two-Speed Drive
- Cup Holder
- High-Back Adjustable Seat
- Integral Access Plate (removable)
- Pilot Joystick Controls
- Lift Arm Support Device
- All-Tach® Attachment Mounting System
- Operator Restraint Bar
- IdealTrax® automatic track tensioning system

OPTIONALE MERKMALE

- Selectable Self-Leveling Hydraulic Lift Action 4
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Cab Enclosure
- Suspension Seat - Mechanical
- Back-Up Alarm
- Engine Block Heater
- Cabin with Heat
- Hydraglide™ Ride Control
- Air Ride Suspension Seat
- High-Flow Auxiliary Hydraulics
- Air Conditioning



One Gehl Way, West Bend, WI 53095
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.