

# V330 GEN:2

COMPACT LOADERS



## Key Features

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Vertical Style Lift Path
- ✓ 4 Cylinder Turbo Diesel Engine
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles with 8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner

## Key Specifications

- ✓ Operating capacity (50%) - 3,300 lbs. (1497 kg)
- ✓ Overall height to top of ROPS - 82" (2083 mm)
- ✓ Gross Power - 72 hp (53.7 kW) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMS / Tier IV
- ✓ 217 ft.-lbs. (294.2 Nm) @ 1625 rpm max torque
- ✓ 131.2" (3332 mm) height to hinge pin
- ✓ 71.6" (1819 mm) machine width - less bucket
- ✓ 9,090 lbs. (4123 kg) operating weight

## SPECIFICATIONS

		METRIC
Capacities	Operating Capacity At 50% Tipping Load	1497 kg
	Operating Weight	4123 kg
	Tipping capacity	2993.71 kg
Weight and dimensions	Wheelbase	1257 mm
	Overall Operating Height - Fully Raised	4369 mm
	Height to Hinge Pin - Fully Raised	3332 mm
	Dump angle at full height	42 °
	Dump height	2502 mm
	Overall length with bucket	3674 mm
	Dump reach - Full height	813 mm
	Rollback at ground	29 °
	Seat to ground height	1041 mm
	Overall width less bucket	1819 mm
	Bucket Width	1880 mm
	Ground clearance	229 mm
	Overall length - Less Bucket	3023 mm
	Clearance Radius - Front with Bucket	2400 mm
	Rear departure angle	25 °
Performances	Travel speed (unladen)	13.50 km/h
	Travel Speed with Two-Speed Option - Maximum	20.10 km/h
Wheels	Standard tires	14.00 x 17.5 HD
Engine	Engine brand	Yanmar
	Engine model	4TNV98CT-CNMS
	Engine norm	Stage IV / Tier 4 Final
	Gross Power	53.70 kW
	Net Power	52.70 kW
	Max. torque / Engine rotation	294.20 Nm / 1625 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	3 kW
Hydraulics	Standard flow - Auxiliary hydraulics	89 l/min
	High-Flow Auxiliary Hydraulics - Option	132 l/min
Tank capacities	Fuel tank	92.70 l
	Hydraulic tank capacity	40 l
	Displacement	3.30 l
Noise and vibration	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	1.07 m/s <sup>2</sup>
	Vibration on hands/arms	< 1.50 m/s <sup>2</sup>



## STANDARD FEATURES

- ROPS/FOPS Level II Overhead Guard
- Hour meter
- Battery charge indicator lamp
- Adjustable 2-inch Seat Belt
- Hydraloc™ Safety System
- Operator Restraint Bar
- Anti-Vandalism Lock Provisions
- Front and Rear - Work Lights
- 12Volt Power Port
- Horn
- Hand/Foot Controls
- High-Back Adjustable Seat
- Gehl T-Bar Controls
- Fuel gauge with low level indicator

## OPTIONAL FEATURES

- Suspension Seat
- Power-A-Tach® Attachment Mounting System
- Ceiling light
- Selectable Self-Leveling Hydraulic Lift Action
- Back-Up Alarm
- Rotating Beacon
- LED Work Lights
- Rear view mirror
- Heat & Defrost
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- Engine Block Heater
- Rear camera with cab display screen
- 3-inch Seatbelt
- Bluetooth car radio
- Swing-out Cab Door

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT