

# R105

# SKID LOADERS




# GEHL®

| Capacities                                           |     | Métrique                    |
|------------------------------------------------------|-----|-----------------------------|
| Rated Operating Capacity                             |     | 476.27 kg                   |
| Rated Operating Capacity with Optional Counterweight |     | 533 kg                      |
| Unladen weight                                       |     | 1905 kg                     |
| Weight and dimensions                                |     |                             |
| Overall Operating Height - Fully Raised              | h27 | 3607 mm                     |
| Height to Hinge Pin - Fully Raised                   | h28 | 2731 mm                     |
| Overall Height to top of ROPS                        | h17 | 1784 mm                     |
| Dump angle at full height                            | a5  | 40 °                        |
| Dump height                                          | h29 | 2083 mm                     |
| Overall length with bucket                           | l16 | 2997 mm                     |
| Dump reach - Full height                             | r6  | 641 mm                      |
| Rollback at ground                                   | a13 | 31 °                        |
| Seat to ground height                                | h30 | 826 mm                      |
| Wheelbase                                            | y   | 876 mm                      |
| Overall width less bucket                            | b1  | 1232 mm                     |
| Bucket Width                                         | e1  | 1372 mm                     |
| Ground clearance                                     | m4  | 159 mm                      |
| Overall length - Less Bucket                         | l2  | 2248 mm                     |
| Clearance Radius - Front with Bucket                 | b18 | 1829 mm                     |
| Clearance Circle - Front without Bucket              | b19 | 1067 mm                     |
| Clearance Circle - Rear                              | wa1 | 1372 mm                     |
| Performances                                         |     |                             |
| Travel speed (unladen)                               |     | 8.26 km/h                   |
| Wheels                                               |     |                             |
| Standard tires                                       |     | 27x8.5x15 HD                |
| Engine                                               |     |                             |
| Engine brand                                         |     | Yanmar                      |
| Engine model                                         |     | 3TNV88C-KMS                 |
| Engine norm                                          |     | Stage IIIA, Stage V, Tier 4 |
| Gross Power                                          |     | 25.50 kW                    |
| Net Power                                            |     | 23.70 kW                    |
| Max. torque / Engine rotation                        |     | 109.40 Nm / 1820 rpm        |
| Power source                                         |     | Diesel                      |
| Battery voltage                                      |     | 12 V                        |
| Starter                                              |     | 2.30 kW                     |
| Hydraulics                                           |     |                             |
| Standard flow - Auxiliary hydraulics                 |     | 55 l/min                    |
| Tank capacities                                      |     |                             |
| Fuel tank                                            |     | 43.18 l                     |
| Hydraulic oil tank capacity                          |     | 30.30 l                     |
| Displacement                                         |     | 1.64 l                      |
| Noise and vibration                                  |     |                             |
| Noise to environment (LwA)                           |     | 101 dB                      |
| Whole-Body Vibration (ISO 2631-1)                    |     | 1.12 m/s <sup>2</sup>       |
| Vibration on hands/arms                              |     | < 1.70 m/s <sup>2</sup>     |

# Équipements

|                                                   |        |
|---------------------------------------------------|--------|
| ---                                               |        |
| Integral Access Plate (removable)                 | Série  |
| Lifting function                                  |        |
| All-Tach® Attachment Mounting System              | Série  |
| Lighting                                          |        |
| Front and Rear - Work Lights                      | Série  |
| Strobe Light                                      | Option |
| Motorization /Power                               |        |
| Battery charge indicator lamp                     | Série  |
| Engine Auto-Shutdown System                       | Option |
| Engine Block Heater                               | Option |
| Fuel gauge with low level indicator               | Série  |
| Operator station                                  |        |
| 12V plug cigarette lighter type                   | Série  |
| 3-inch Seatbelt                                   | Option |
| Ceiling light                                     | Option |
| Enclosed Cab with Heat and Defrost                | Option |
| Foot and Hand Throttles (Dual Joystick and T-bar) | Série  |
| High-Back Adjustable Seat                         | Série  |
| Radio                                             | Option |
| Suspension Seat                                   | Option |
| Secondary functions                               |        |
| Counterweight                                     | Option |
| Security                                          |        |
| Anti-Vandalism Lock Provisions                    | Série  |
| Back-Up Alarm                                     | Série  |
| Battery cut-off                                   | Option |
| Easy Manager                                      | Option |
| Horn                                              | Option |
| Hour meter                                        | Série  |
| Hydraloc™ Safety System                           | Série  |
| Lift Arm Support Device                           | Série  |
| Operator Restraint Bar                            | Série  |
| ROPS/FOPS Level II Overhead Guard                 | Série  |



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend