

# RT135

COMPACT LOADERS



## Key Features

- ✓ Compact Dimensions
- ✓ Pilot Joystick Controls
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ All-Tach Attachment System (Universal Type)
- ✓ ROPS/FOPS Level II

## Key Specifications

- ✓ 1,350 lbs. (612 kg) Rated Operating Capacity (35%)
- ✓ 46.6 hp (34.3 kW) Yanmar Engine / Tier IV
- ✓ 110" (2794 mm) Height to Hinge Pin
- ✓ 57" (1448 mm) Overall Machine Width
- ✓ 76" (1930 mm) Overall Height

## SPECIFICATIONS

		IMPERIAL
Capacities	Operating Weight	6510 lb
	Operating Capacity at 35% Tipping Load	1350 lb
	Operating Capacity At 50% Tipping Load	1929 lb
	Tipping capacity	3858 lb
Weight and dimensions	Overall Operating Height - Fully Raised	144 in
	Height to Hinge Pin - Fully Raised	110 in
	Dump angle at full height	40 °
	Overall Height to top of ROPS	76 in
	Overall length with bucket	121 in
	Overall Length without Bucket	93 in
	Specified Height	30 in
	Reach at Specified Height	59 in
	Dump angle at specified height	75 °
	Carry Position	6 in
	Maximum Rollback Angle at Carry Position	28 °
	Digging Position	0.71 in
	Angle of Departure with STD Counterweight	28 °
	Ground clearance	8 in
	Track gauge	45 in
	Track Shoe Width	12 in
	Crawler base	46 in
Overall width less bucket	57 in	
Bucket Width	60 in	
Clearance Radius - Front with Bucket	76 in	
Track Type / Track Rollers / Roller Type	Rubber / 4 / Steel	
Performances	Ground Speed - Single Speed	6 mph
	Drawbar Pull/Tractive Effort	7161 lb
	Bucket Breakout - Tilt Cylinder	3501 lb
	Bucket Breakout - Lift Cylinder	3730 lb
Engine	Engine brand	Yanmar
	Engine model	4TNV88
	Motor Type	Radial Piston
	Gross Power / Power	46.60 Hp @ 2500 rpm
	Battery voltage	12 V
	Cold Cranking Amps at Temperature (CCA)	800 A
Hydraulics	Alternator - Voltage / Ampere	12 V / 100 A
	Standard flow - Auxiliary hydraulics	17 US gpm
Tank capacities	Oil Pan Capacity	2 US gal
	Hydraulic tank capacity	9 US gal
	Fuel tank	16 US gal
	Displacement / Number of cylinders	0.58 US gal / 4



## STANDARD FEATURES

- Hour meter
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Swing-Out Cooler
- Hydraloc™ Safety System
- Lift Arm Support Device
- Back-Up Alarm
- ROPS/FOPS Level II Overhead Guard
- Horn
- Hand/Foot Controls
- High-Back Adjustable Seat
- All-Tach® Attachment Mounting System
- Operator Restraint Bar

## OPTIONAL FEATURES

- Counterweight
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Back-Up Alarm
- Engine Block Heater
- Suspension Seat - Air Ride
- Strobe Light
- Bluetooth car radio
- Rear camera with screen in cab
- Cabin with Heat and Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT