

# R135 GEN-2

# SKID LOADERS



**GEHL**®

Capacities		Imperial
Operating Capacity At 50% Tipping Load		1350 lb
Rated Operating Capacity with Optional Counterweight		1499 lb
Operating Weight		5255 lb
Tipping capacity		2700 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	144 in
Height to Hinge Pin - Fully Raised	h28	110 in
Overall Height to top of ROPS	h17	76 in
Dump angle at full height	a5	40 °
Dump height	h29	83 in
Overall length with bucket	l16	121 in
Dump reach - Full height	r6	23 in
Rollback at ground	a13	28 °
Seat to ground height	h30	34 in
Wheelbase	y	37 in
Overall width less bucket	b1	54 in
Bucket Width	e1	54 in
Ground clearance	m4	8 in
Overall length - Less Bucket	l2	93 in
Clearance Radius - Front with Bucket	b18	73 in
Clearance Circle - Front without Bucket	b19	44 in
Clearance Circle - Rear	wa1	54 in
Performances		
Travel speed (unladen)		8 mph
Wheels		
Standard tires		10.00 x 16.5 HD
Engine		
Engine brand		Yanmar
Engine model		4TNV88C
Engine norm		Stage IV / Tier 4 Final
Gross Power		34.30 kW
Net Power		33.20 kW
Max. torque / Engine rotation		108 ft/lbs / 1820 rpm
Power source		Diesel
I.C. Engine power rating		46.60 Hp
Battery voltage		12 V
Starter		2.30 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		17 US gpm
Tank capacities		
Fuel tank		16 US gal
Hydraulic tank capacity		9 US gal
Displacement		0.58 US gal
Noise and vibration		
Noise to environment (LwA)		101 dB
Whole-Body Vibration (ISO 2631-1)		0.81 m/s <sup>2</sup>
Vibration on hands/arms		< 1.77 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend