

# R135 GEN:2

# SKID LOADERS



# GEHL®

Capacities		Metric
Rated Operating Capacity		612.34 kg
Rated Operating Capacity with Optional Counterweight		680 kg
Unladen weight		2383.62 kg
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	3670.30 mm
Height to Hinge Pin – Fully Raised	h28	2790 mm
Overall Height to top of ROPS	h17	1930 mm
Dump angle at full height	a5	40 °
Dump height	h29	2120 mm
Overall length with bucket	l16	3073.40 mm
Dump reach - Full height	r6	591 mm
Rollback at ground	a13	28 °
Seat to ground height	h30	871.22 mm
Wheelbase	y	950 mm
Overall width less bucket	b1	1364 mm
Bucket Width	e1	1372 mm
Ground clearance	m4	201 mm
Overall length - Less Bucket	l2	2359.66 mm
Clearance Radius - Front with Bucket	b18	1842 mm
Clearance Circle - Front without Bucket	b19	1120 mm
Clearance Circle - Rear	wa1	1372 mm
Performances		
Travel speed (unladen)		12.90 km/h
Wheels		
Standard tires		10.00x16.5 HD
Engine		
Engine brand		Yanmar
Engine model		4TNV88C
Engine norm		Stage IIIA, Stage V, Tier 4 final
Gross Power		34.30 kW
Net Power		33.20 kW
Max. torque / Engine rotation		146.20 Nm / 1820 rpm
Power source		Diesel
Battery voltage		12 V
Starter		2.30 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		63.60 l/min
Tank capacities		
Fuel tank		59.40 l
Displacement		2.19 l
Noise and vibration		
Noise to environment (LwA)		101 dB
Whole-Body Vibration (ISO 2631-1)		0.81 m/s <sup>2</sup>
Vibration on hands/arms		< 1.77 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend