

R135 GEN:2

COMPACT LOADERS



Key Features

- ✓ Low Effort Control Choices
- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Self-Leveling Hydraulic Lift-Action
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar or Hand/Foot Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat

Key Specifications

- ✓ Operating capacity (50%) - 1,350 lbs. (612 kg)
- ✓ Overall height to top of ROPS - 76" (1930 mm)
- ✓ Gross Power - 46.6 hp (34.3 kW) @ 2800 rpm
- ✓ Yanmar / 4TNV88C-KMS / Tier IV
- ✓ 108 ft.-lbs (146.2 Nm) @ 1820 rpm max torque
- ✓ 110" (2790 mm) height to hinge pin
- ✓ 53.7" (1364 mm) machine width - less bucket
- ✓ 5,130 lbs. (2327 kg) operating weight

ESPECIFICACIONES

		MÉTRICO
Capacities	Operating Capacity At 50% Tipping Load	612.34 kg
	Rated Operating Capacity with Optional Counterweight	680 kg
	Operating Weight	2383.62 kg
	Tipping capacity	1224.69 kg
Weight and dimensions	Wheelbase	950 mm
	Overall Operating Height - Fully Raised	3670.30 mm
	Height to Hinge Pin - Fully Raised	2790 mm
	Dump angle at full height	40 °
	Dump height	2120 mm
	Overall length with bucket	3073.40 mm
	Dump reach - Full height	591 mm
	Seat to ground height	871.22 mm
	Overall width less bucket	1364 mm
	Bucket Width	1372 mm
	Ground clearance	201 mm
	Overall length - Less Bucket	2359.66 mm
	Clearance Radius - Front with Bucket	1842 mm
	Rear departure angle	25 °
Performances	Travel speed (unladen)	12.90 km/h
Wheels	Standard tires	10.00 x 16.5 HD
Engine	Engine brand	Yanmar
	Engine model	4TNV88
	Engine norm	Stage IIIA / Interim Tier 4
	Gross Power	34.30 kW
	Net Power	33.20 kW
	Max. torque / Engine rotation	146.20 Nm / 1820 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	2.30 kW
Hydraulics	Standard flow - Auxiliary hydraulics	63.60 l/min
Tank capacities	Fuel tank	59.40 l
	Hydraulic tank capacity	34.80 l
	Displacement	2.19 l
Noise and vibration	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	0.81 m/s ²
	Vibration on hands/arms	< 1.77 m/s ²



One Gehl Way, West Bend, WI 53095
Teléfono: (262) 334-9461



GEHL COMPACT EQUIPMENT

® Representa registro en los Estados Unidos. Las marcas comerciales pueden o no estar registradas en otros países.