

Ficha técnica :

# ME 315 FOB



 **MANITOU**  
HANDLING YOUR WORLD

| Technical characteristics |   |           | Métrico                  |
|---------------------------|---|-----------|--------------------------|
| 1.1                       | Manufacturer  |           | Manitou                  |
| 1.2                       | Model Name  |           | ME 315 FOB               |
| 1.3                       | Power source  |           | Electrical               |
| 1.4                       | Operator type   |           | Seated                   |
| 1.5                       | Max. capacity   | Q         | 1500 kg                  |
| 1.6                       | Load center of gravity  | c         | 500 mm                   |
| 1.8                       | Load distance, centre of drive axle to fork                     | x         | 355 mm                   |
| 1.9                       | Wheelbase   | y         | 1250 mm                  |
| Weight                    |   |           |                          |
| 2.1                       | Service weight  |           | 2860 kg                  |
| 2.2                       | Weight on front axle (laden) / rear axle (laden)                |           | 3600 kg / 560 kg         |
| 2.3                       | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 1350 kg / 1510 kg        |
| Wheels                    |   |           |                          |
| 3.1                       | Tires type  |           | Solid tires              |
| 3.2                       | Dimensions of front wheels                                      |           | 18 x 7 - 8               |
| 3.3                       | Dimensions of rear wheels                                       |           | 15 x 4.5 - 8             |
| 3.5                       | Number of front wheels / rear wheels                            |           | 2 / 1                    |
| 3.5.2                     | Number of drive wheels  |           | 2                        |
| 3.6                       | Front wheel gauge   | b10       | 910 mm                   |
| 3.7                       | Rear wheel gauge  | b11       | 175 mm                   |
| Dimensions                |   |           |                          |
| 4.7                       | Height of overhead guard (cabin)                                | h6        | 2040 mm                  |
| 4.8                       | Seat height/stand height  | h7        | 1000 mm                  |
| 4.12                      | Height of towing bar (coupling height)                          | h10       | 500 mm                   |
| 4.19                      | Overall length  | l1        | 2860 mm                  |
| 4.20                      | Length to face of forks   | l2        | 1790 mm                  |
| 4.21                      | Overall width   | b1        | 1086 mm                  |
| 4.22                      | Forks section / width / length                                  | s / e / l | 100 mm x 1150 mm x 35 mm |
| 4.23                      | Fork carriage ISO 2328 (class/form) A/B                         |           | 2A                       |
| 4.24                      | Fork carriage width   | b3        | 1000 mm                  |
| 4.32                      | Ground clearance at centre of wheelbase                         | m2        | 100 mm                   |
| 4.33                      | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 3138 mm                  |
| 4.34                      | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 3262 mm                  |
| 4.35                      | Turning radius  | Wa        | 1452 mm                  |
| 4.36                      | Internal turning radius (over tyres)                            | b13       | 0 mm                     |
| Performances              |   |           |                          |
| 5.1                       | Travel speed (laden / unladen)                                  |           | 16 km/h-16 km/h          |
| 5.2                       | Lifting speed (laden / unladen)                                 |           | 0.40 m/s-0.47 m/s        |
| 5.3                       | Lowering speed (laden / unladen)                                |           | 0.46 m/s-0.45 m/s        |
| 5.7                       | Gradeability (laden / unladen)                                  |           | 16 % / 18 %              |
| 5.10                      | Service brake   |           | Oil bath                 |
| Engine                    |   |           |                          |
| 6.1                       | Number of drive motor / Drive motor rating S2 60 min            |           | 2 / 4.50 kW              |
| 6.2                       | Lift motor rating at S3 15%                                     |           | 8.60 kW                  |
| 6.3                       | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43531 A               |
| 6.4                       | Battery voltage / capacity                                      |           | 48 V / 460 Ah            |
| 6.6                       | Energy consumption according to VDI cycle (kWh/h)               |           | 4.30 kWh/h               |
| Miscellaneous             |   |           |                          |
| 8.1                       | Type of drive control   |           | Electronic               |
| 8.2                       | Working hydraulic pressure for attachments                      |           | 155 bar                  |
| 8.3                       | Oil flow rate for attachments                                   |           | 35 l/min                 |
| 8.4                       | Measured/guaranteed mean noise level at the ear of the operator |           | < 70 dB                  |
| 8.4                       | Sound level at the driver's ear according to DIN 12 053         |           | 70 dB                    |

### ME 315 FOB - Diagrama dimensional







**Oficina Central**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes