

Ficha técnica :

ME 418 FOB



 **MANITOU**
HANDLING YOUR WORLD

| Technical characteristics | | | Métrico |
|---------------------------|---|-----------|--------------------------|
| 1.1 | Manufacturer | | Manitou |
| 1.2 | Model Name | | ME 418 FOB |
| 1.3 | Power source | | Electrical |
| 1.4 | Operator type | | Seated |
| 1.5 | Max. capacity | Q | 1800 kg |
| 1.6 | Load center of gravity | c | 500 mm |
| 1.8 | Load distance, centre of drive axle to fork | x | 411 mm |
| 1.9 | Wheelbase | y | 1380 mm |
| Weight | | | |
| 2.1 | Service weight | | 3070 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 4350 kg / 520 kg |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 1400 kg / 1670 kg |
| Wheels | | | |
| 3.1 | Tires type | | Solid tires |
| 3.2 | Dimensions of front wheels | | 21 x 8-9 |
| 3.3 | Dimensions of rear wheels | | 5.00-8 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 938 mm |
| 3.7 | Rear wheel gauge | b11 | 898 mm |
| Dimensions | | | |
| 4.7 | Height of overhead guard (cabin) | h6 | 2130 mm |
| 4.8 | Seat height/stand height | h7 | 1045 mm |
| 4.12 | Height of towing bar (coupling height) | h10 | 275 mm |
| 4.19 | Overall length | l1 | 3248 mm |
| 4.20 | Length to face of forks | l2 | 2098 mm |
| 4.21 | Overall width | b1 | 1138 mm |
| 4.22 | Forks section / width / length | s / e / l | 100 mm x 1150 mm x 35 mm |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | 2A |
| 4.24 | Fork carriage width | b3 | 1000 mm |
| 4.31 | Ground clearance below mast | m1 | 100 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 110 mm |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 3511 mm |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 3711 mm |
| 4.35 | Turning radius | Wa | 1900 mm |
| 4.36 | Internal turning radius (over tyres) | b13 | 680 mm |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 13.50 km/h-14 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 0.29 m/s-0.44 m/s |
| 5.3 | Lowering speed (laden / unladen) | | 0.49 m/s-0.48 m/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 1200 daN / 1100 daN |
| 5.7 | Gradeability (laden / unladen) | | 12 % / 13 % |
| 5.10 | Service brake | | Hydraulic |
| Engine | | | |
| 6.1 | Drive motor rating S2 60 min | | 8 kW |
| 6.2 | Lift motor rating at S3 15% | | 8.60 kW |
| 6.3 | Battery according to DIN 43531/35/36 A, B, C | | DIN43531 A |
| 6.4 | Battery voltage / capacity | | 48 V / 465 Ah |
| 6.6 | Energy consumption according to VDI cycle (kWh/h) | | 4.60 kWh/h |
| Miscellaneous | | | |
| 8.1 | Type of drive control | | Electronic |
| 8.2 | Working hydraulic pressure for attachments | | 175 bar |
| 8.3 | Oil flow rate for attachments | | 35 l/min |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 71 dB |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | 71 dB |

ME 418 FOB - Diagrama dimensional





Oficina Central

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes