

Fiche technique :

# ME 430 FOB



Technical characteristics		Métrique	
1.1	Manufacturer		Manitou
1.2	Model Name		ME 430 FOB
1.3	Power source		Electrical
1.4	Operator type		Seated
1.5	Max. capacity	Q	3000 kg
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	445 mm
1.9	Wheelbase	y	1750 mm
Weight			
2.1	Service weight		5250 kg
2.2	Weight on front axle (laden) / rear axle (laden)		7340 kg / 980 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2572 kg / 2578 kg
Wheels			
3.1	Tires type		Solid tires
3.2	Dimensions of front wheels		23 x 9-10
3.3	Dimensions of rear wheels		18 x 7-8
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		2
3.6	Front wheel gauge	b10	1073 mm
3.7	Rear wheel gauge	b11	960 mm
Dimensions			
4.7	Height of overhead guard (cabin)	h6	2240 mm
4.8	Seat height/stand height	h7	1190 mm
4.12	Height of towing bar (coupling height)	h10	625 mm
4.19	Overall length	l1	3645 mm
4.20	Length to face of forks	l2	2495 mm
4.21	Overall width	b1	1275 mm
4.22	Forks section / width / length	s / e / l	45 mm x 122 mm x 1150 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		3A
4.24	Fork carriage width	b3	1100 mm
4.31	Ground clearance below mast	m1	105 mm
4.32	Ground clearance at centre of wheelbase	m2	115 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4045 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4245 mm
4.35	Turning radius	Wa	2400 mm
4.36	Internal turning radius (over tyres)	b13	730 mm
Performances			
5.1	Travel speed (laden / unladen)		19 km/h-20 km/h
5.2	Lifting speed (laden / unladen)		0.42 m/s-0.54 m/s
5.3	Lowering speed (laden / unladen)		0.47 m/s-0.42 m/s
5.5	Drawbar pull (Laden / Unladen)		1740 daN / 1680 daN
5.7	Gradeability (laden / unladen)		14 % / 20 %
5.10	Service brake		Oil bath
Engine			
6.1	Drive motor rating S2 60 min		18.50 kW
6.2	Lift motor rating at S3 15%		25.40 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43536 A
6.4	Battery voltage / capacity		80 V / 700 Ah
6.6	Energy consumption according to VDI cycle (kWh/h)		11.50 kWh/h
Miscellaneous			
8.1	Type of drive control		Electronic
8.2	Working hydraulic pressure for attachments		210 bar
8.3	Oil flow rate for attachments		65 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 72 dB
8.4	Sound level at the driver's ear according to DIN 12 053		72 dB

### ME 430 FOB - Schémas d'encombrement



## Caractéristiques des mâts et capacités résiduelles

Full Visibility Duplex (FVD)	FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 43	FVD 45	FVD 48	FVD 50
α - Mast/fork carriage tilt, forward °	5	5	5	5	5	5	5	5	5
β - Mast/fork carriage tilt, backward °	8	8	8	8	8	5	5	5	5
h1 - Mast lowered height mm	2235	2385	2485	285	2835	2985	3085	3235	3335
h2 - Mast free lift mm	145	145	145	145	145	145	145	145	145
h3 - Mast lifting height mm	3000	3300	3500	3700	4000	4300	4500	4800	5000
h4 - Mast extended height mm	3838	4138	4338	4538	4838	5138	5338	5638	5838
Residual capacity at max height kg	3000	3000	3000	3000	3000	3000	3000	3000	3000
Residual capacity with integrated side shift at max height kg	3000	3000	3000	3000	3000	3000	3000	3000	3000
Residual capacity with hooked-on side shift at max height kg	3000	3000	3000	3000	3000	3000	2950	2900	2800
Height at max capacity mm	3000	3300	3500	3700	4000	4300	4500	4800	5000
Height at max capacity with integrated sideshift mm	3000	3300	3500	3700	4000	4300	4500	4800	5000

Free Lift Duplex (FLD)	FLD 30	FLD 33	FLD 37	FLD 40
α - Mast/fork carriage tilt, forward °	5	5	5	5
β - Mast/fork carriage tilt, backward °	8	8	8	8
h1 - Mast lowered height mm	2135	2285	2485	2685
h2 - Mast free lift mm	1275	1425	1625	1825
h3 - Mast lifting height mm	3000	3300	3700	4000
h4 - Mast extended height mm	3860	4160	4560	4860
Residual capacity at max height kg	3000	3000	3000	3000
Residual capacity with integrated side shift at max height kg	3000	3000	3000	3000
Residual capacity with hooked-on side shift at max height kg	3000	3000	3000	3000
Height at max capacity mm	3000	3300	3700	4000
Height at max capacity with integrated sideshift mm	3000	3300	3700	4000

Free Lift Triplex (FLT)	FLT 40	FLT 43	FLT 48	FLT 50	FLT 55	FLT 60
α - Mast/fork carriage tilt, forward °	5	5	5	5	5	5
β - Mast/fork carriage tilt, backward °	5	5	5	5	5	5
h1 - Mast lowered height mm	2035	2135	2285	2385	2585	2835
h2 - Mast free lift mm	1250	1350	1500	1600	1800	2050
h3 - Mast lifting height mm	4000	4300	4800	5000	5500	6000
h4 - Mast extended height mm	4785	5085	5585	5785	6285	6785
Residual capacity at max height kg	3000	3000	3000	3000	2900	2700
Residual capacity with integrated side shift at max height kg	3000	3000	3000	2900	2800	2650
Residual capacity with hooked-on side shift at max height kg	2900	2900	2850	2750	2550	2450
Height at max capacity mm	4000	4300	4800	5000	4000	4000
Height at max capacity with integrated sideshift mm	4000	4300	4800	4000	4000	4000



**Siège Social**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



Cette publication présente le descriptif des versions et possibilités de configuration des produits Manitou qui peuvent différer en équipement. Les équipements présentés dans cette brochure peuvent être de série, en option, ou non disponibles suivant les versions. Manitou se réserve le droit, à tout moment et sans préavis, de modifier les spécifications décrites et représentées. Les spécifications portées n'engagent pas le constructeur. Pour plus de détails, contactez votre concessionnaire Manitou. Document non contractuel. Présentation des produits non contractuelle. Liste des spécifications non exhaustive. Les logos ainsi que l'identité visuelle de l'entreprise sont la propriété de Manitou et ne peuvent être utilisés sans autorisation. Tous droits réservés. Les photos et schémas contenus dans la présente brochure ne sont fournis qu'à des fins de consultation et à titre indicatif.

Manitou BF SA - Société anonyme à conseil d'administration - Capital social : 39 668 399 euros - 857 802 508 RCS Nantes