

Технический паспорт ТЕХНИЧЕСКОЕ ОПИСАНИЕ :

# ME 430 FOB

---



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Метрический              |
|-------|-----------------------------------------------------------------|-----------|--------------------------|
| 1.1   | Manufacturer                                                    |           | Manitou                  |
| 1.2   | Model Name                                                      |           | ME 430 FOB               |
| 1.3   | Power source                                                    |           | Electrical               |
| 1.4   | Operator type                                                   |           | Seated                   |
| 1.5   | Max. capacity                                                   | Q         | 3000 kg                  |
| 1.6   | Load center of gravity                                          | c         | 500 mm                   |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 445 mm                   |
| 1.9   | Wheelbase                                                       | y         | 1750 mm                  |
|       | <b>Weight</b>                                                   |           |                          |
| 2.1   | Service weight                                                  |           | 5250 kg                  |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 7340 kg / 980 kg         |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 2572 kg / 2578 kg        |
|       | <b>Wheels</b>                                                   |           |                          |
| 3.1   | Tires type                                                      |           | Solid tires              |
| 3.2   | Dimensions of front wheels                                      |           | 23 x 9-10                |
| 3.3   | Dimensions of rear wheels                                       |           | 18 x 7-8                 |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 2                    |
| 3.5.2 | Number of drive wheels                                          |           | 2                        |
| 3.6   | Front wheel gauge                                               | b10       | 1073 mm                  |
| 3.7   | Rear wheel gauge                                                | b11       | 960 mm                   |
|       | <b>Dimensions</b>                                               |           |                          |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2240 mm                  |
| 4.8   | Seat height/stand height                                        | h7        | 1190 mm                  |
| 4.12  | Height of towing bar (coupling height)                          | h10       | 625 mm                   |
| 4.19  | Overall length                                                  | l1        | 3645 mm                  |
| 4.20  | Length to face of forks                                         | l2        | 2495 mm                  |
| 4.21  | Overall width                                                   | b1        | 1275 mm                  |
| 4.22  | Forks section / width / length                                  | s / e / l | 45 mm x 122 mm x 1150 mm |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 3A                       |
| 4.24  | Fork carriage width                                             | b3        | 1100 mm                  |
| 4.31  | Ground clearance below mast                                     | m1        | 105 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 115 mm                   |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 4045 mm                  |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4245 mm                  |
| 4.35  | Turning radius                                                  | Wa        | 2400 mm                  |
| 4.36  | Internal turning radius (over tyres)                            | b13       | 730 mm                   |
|       | <b>Performances</b>                                             |           |                          |
| 5.1   | Travel speed (laden / unladen)                                  |           | 19 km/h-20 km/h          |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.42 m/s-0.54 m/s        |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.47 m/s-0.42 m/s        |
| 5.5   | Drawbar pull (Laden / Unladen)                                  |           | 1740 daN / 1680 daN      |
| 5.7   | Gradeability (laden / unladen)                                  |           | 14 % / 20 %              |
| 5.10  | Service brake                                                   |           | Oil bath                 |
|       | <b>Engine</b>                                                   |           |                          |
| 6.1   | Drive motor rating S2 60 min                                    |           | 18.50 kW                 |
| 6.2   | Lift motor rating at S3 15%                                     |           | 25.40 kW                 |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | DIN43536 A               |
| 6.4   | Battery voltage / capacity                                      |           | 80 V / 700 Ah            |
| 6.6   | Energy consumption                                              |           | 11.50 kWh                |
|       | <b>Miscellaneous</b>                                            |           |                          |
| 8.1   | Type of drive control                                           |           | Electronic               |
| 8.2   | Working hydraulic pressure for attachments                      |           | 210 bar                  |
| 8.3   | Oil flow rate for attachments                                   |           | 65 l/min                 |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 72 dB                  |
| 8.4   | Sound level at the driver's ear according to DIN 12 053         |           | 72 dB                    |

## ME 430 FOB - габаритный чертеж



# Характеристики мачт и начальная емкость

| Full Visibility Duplex (FVD)                               |    | FVD 30 | FVD 33 | FVD 35 | FVD 37 | FVD 40 | FVD 43 | FVD 45 | FVD 48 | FVD 50 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      | 8      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2235   | 2385   | 2485   | 285    | 2835   | 2985   | 3085   | 3235   | 3335   |
| h2 - Mast free lift                                        | mm | 145    | 145    | 145    | 145    | 145    | 145    | 145    | 145    | 145    |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |
| h4 - Mast extended height                                  | mm | 3838   | 4138   | 4338   | 4538   | 4838   | 5138   | 5338   | 5638   | 5838   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with hooked-on side shift at max height  | kg | 3000   | 3000   | 3000   | 3000   | 3000   | 3000   | 2950   | 2900   | 2800   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3500   | 3700   | 4000   | 4300   | 4500   | 4800   | 5000   |

| Free Lift Duplex (FLD)                                     |    | FLD 30 | FLD 33 | FLD 37 | FLD 40 |
|------------------------------------------------------------|----|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 8      | 8      | 8      | 8      |
| h1 - Mast lowered height                                   | mm | 2135   | 2285   | 2485   | 2685   |
| h2 - Mast free lift                                        | mm | 1275   | 1425   | 1625   | 1825   |
| h3 - Mast lifting height                                   | mm | 3000   | 3300   | 3700   | 4000   |
| h4 - Mast extended height                                  | mm | 3860   | 4160   | 4560   | 4860   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 3000   |
| Residual capacity with hooked-on side shift at max height  | kg | 3000   | 3000   | 3000   | 3000   |
| Height at max capacity                                     | mm | 3000   | 3300   | 3700   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 3000   | 3300   | 3700   | 4000   |

| Free Lift Triplex (FLT)                                    |    | FLT 40 | FLT 43 | FLT 48 | FLT 50 | FLT 55 | FLT 60 |
|------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                           | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| Mast/fork carriage tilt, backward                          | °  | 5      | 5      | 5      | 5      | 5      | 5      |
| h1 - Mast lowered height                                   | mm | 2035   | 2135   | 2285   | 2385   | 2585   | 2835   |
| h2 - Mast free lift                                        | mm | 1250   | 1350   | 1500   | 1600   | 1800   | 2050   |
| h3 - Mast lifting height                                   | mm | 4000   | 4300   | 4800   | 5000   | 5500   | 6000   |
| h4 - Mast extended height                                  | mm | 4785   | 5085   | 5585   | 5785   | 6285   | 6785   |
| Residual capacity at max height                            | kg | 3000   | 3000   | 3000   | 3000   | 2900   | 2700   |
| Residual capacity with integrated side shift at max height | kg | 3000   | 3000   | 3000   | 2900   | 2800   | 2650   |
| Residual capacity with hooked-on side shift at max height  | kg | 2900   | 2900   | 2850   | 2750   | 2550   | 2450   |
| Height at max capacity                                     | mm | 4000   | 4300   | 4800   | 5000   | 4000   | 4000   |
| Height at max capacity with integrated sideshift           | mm | 4000   | 4300   | 4800   | 4000   | 4000   | 4000   |

**Головной офис**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France (Франция)

Телефон: 00 33 (0)2 40 09 10 11 - Факс: 00 33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)

В данной брошюре описываются версии конфигурации и опции продуктов Manitou, которые могут отличаться в зависимости от оборудования. Описанное в данной брошюре оборудование может, в зависимости от версии, быть стандартным, опциональным или недоступным. Компания Manitou оставляет за собой право в любое время изменять приведенные и описанные характеристики без предварительного уведомления. Указанные технические характеристики не являются обязательными для производителя. Для получения дополнительной информации обратитесь к своему дилеру Manitou. Этот документ не имеет обязывающего, договорного характера. Описание продукции не имеет обязывающего, договорного характера. Список технических характеристик не является исчерпывающим. Логотипы и средства визуальной идентификации являются собственностью Manitou, их несанкционированное использование запрещено. Все права защищены. Фотографии и схемы в этой брошюре предоставлены только для ознакомления и в качестве справочной информации.

Manitou BF SA — Компания с ограниченной ответственностью и советом директоров — Акционерный капитал: 39 668 399 евро — Номер 857 802 508 в Реестре коммерсантов и предприятий Нанта